

# SHENANDOAH COUNTY GROUNDWATER

PRESENT CONDITIONS
AND PROSPECTS

by

Kenneth R. Hinkle and R. McChesney Sterrett

**VALLEY REGIONAL OFFICE** 




STATE WATER CONTROL BOARD
BUREAU OF WATER CONTROL MANAGEMENT

Richmond, Virginia

Planning Bulletin 306

**July 1977** 





# GROUNDWATER OF SHENANDOAH COUNTY, VIRGINIA



Ву

Kenneth R. Hinkle

and

R. McChesney Sterrett VALLEY REGIONAL OFFICE

VIRGINIA STATE WATER CONTROL BOARD BUREAU OF WATER CONTROL MANAGEMENT Richmond, Virginia Planning Bulletin 306 July 1977

					**
					L.
					ę
					us u
			•		

# TABLE OF CONTENTS

		Page
	LIST OF PLATES	
	LIST OF TABLES	•
	ACKNOWLEDGEMENTS	хi
	FOREWORD	xiii
	ABSTRACT	xv
CHAPTER	· ·	
I	INTRODUCTION	1
	Background	1
•	Purpose and Scope of Report	2
	Methods of Investigation	2
	Previous Investigations	6
	Water Well Numbering System	7
II	PHYSICAL SETTING	9
	Physiography	9
	Drainage	10
	Climate	10
	Soils and Vegetation	13
III	HYDROGEOLOGY	15
	The Hydrologic Cycle	15
	Geology and Groundwater	16
	Hydrogeology of Shenandoah County	21
	Geologic Setting	21
•	Geologic Formations and	25

	TABLE OF CONTENTS (Continued)	Page
HAPTER		rage
III	Geologic Structure	27
	Groundwater Movement and Storage	28
	Movement	. 31
	Storage	32
IV	GROUNDWATER POTENTIAL AND DEVELOPMENT	35
	Groundwater Potential	35
	Terrace and Alluvial Deposits	35
	Cambro-Ordovician Formations	36
	Silurian and Devonian Shale and Sandstone Formations	40
	Groundwater Development	40
	Public Systems	41
	Industrial Systems	45
	Domestic Wells	47
	Groundwater Development Problems	47
	Well Interference	48
	Sinkhole Collapse	48
	Mud Seams	49
٧	GROUNDWATER QUALITY	51
	Introduction	51
	Groundwater Quality By Hydrogeologic Area	52
	Central Valley Area	52
	Western Highlands and Massanutten Range	60

	TABLE OF CONTENTS (Continued)	
CHAPTER		Page
V	Groundwater Contamination	61
	Methods of Contamination	61
•	Sources of Contamination	63
VI	CONCLUSIONS AND RECOMMENDATIONS	65
	Conclusions	65
	Recommendations	66
	APPENDIX A	A-1
	Key Water Wells in Shenandoah County	A-3
	APPENDIX B	B-1
	Summary of Water Well Data for Shenandoah County	B-3
	APPENDIX C	C-1
	Summary of Groundwater Quality Analyses for Shenandoah County	C-3

GLOSSARY OF TERMS

BIBLIOGRAPHY

# LIST OF PLATES

Plate No	<b>).</b>	Page
	Groundwater Availability in Virginia	Frontispiece
1	Index Map of Shenandoah County	3
2	Physical Characteristics of Shenandoah County	11
3	The Hydrologic Cycle	16
4	Examples of Rock Porosity	18
5	Structural Influences in Groundwater Availability	20
6	Fractures Influence Yield From Carbonate Rocks	21
7	Hydrogeologic Map of Shenandoah County	23
8	Groundwater Potential in Shenandoah County	37
9	Groundwater Development in Shenandoah County	43
10	Groundwater Hardness Trends in Shenandoah County	55
11	Trends of Iron Concentration in Groundwater, Shenandoah County	57
12	Groundwater Contamination Through Sinkholes	62
13	Virginia State Water Control Board Offices	End Flap

# LIST OF TABLES

Table No	•	Page
1 .	1976 Weather Data Recorded at Woodstock, VA	13
2	Geologic Formations and Their Water- Bearing Properties, Shenandoah County	29
3	Average Yield (GPM) By Well Depth For The Aquifer Systems of Shenandoah County	42
4	Public Groundwater Systems in Shenandoah County	45
5	Major Industrial Groundwater Users in Shenandoah County	46
6	Industrial Well Statistics, Shenandoah County	46
7	Groundwater Quality Parameters	53
8	Groundwater Quality Parameters: Average Values (MG/L) By Hydrogeologic Area,	54

120 120 130

#### **ACKNOWLEDGEMENTS**

Appreciation is extended to the citizens of Shenandoah County for permitting water samples to be collected from their wells and springs and for supplying much of the information contained in this report. Well drilling contractors who have been especially cooperative in supplying information include Burner Well Drilling, Dellinger Well Drilling, and Shenandoah Construction Company.

Quality data and selected pumpage data on public groundwater supplies were obtained from the Virginia Department of Health.

The Soil Conservation Service provided maps and charts, and a portion of the hydrologic and climatic information was provided by the Virginia Water Resources Research Center at Virginia Polytechnic Institute and State University in Blacksburg.

Control of the Contro

the Marian and the second of the second

er fan de komponier en de komp

#### **FOREWORD**

This report is one of a series intended to identify the groundwater resources of each county in the Commonwealth. The purpose is to provide all groundwater users, including private citizens, developers, investors, well drilling contractors, government officials, professionals and consultants, with a complete picture of the groundwater situation as it presently exists throughout Virginia.

Prospective groundwater users and anyone else interested in the development and protection of groundwater hopefully will gain insight into the opportunities and advantages inherent in this invaluable natural resource.

The State Water Control Board remains available for information, assistance and governmental action.

en de la companya de la co

# GROUNDWATER RESOURCES OF SHENANDOAH COUNTY, VIRGINIA

by

# R. McChesney Sterrett ABSTRACT

The groundwater resources of Shenandoah County offer a reliable source of high quality water for public, industrial and domestic use. Present groundwater development is minimal and is estimated to be in excess of three million gallons per day. The majority of the development has occurred in the Cambro-Ordovician carbonates, though these rocks are not necessarily the most productive. The younger Martinsburg shales have been developed to a lesser extent. The Silurian and Devonian shales and sandstones which comprise the Massanutten Range and the western portion of the County have seen very limited development.

It is estimated that present groundwater development can be tripled without adverse effects as long as responsible management practices are observed. Areas of maximum potential are areas where the Central Valley formations are overlain by alluvial and terrace deposits. Most notable is a stretch extending from New Market to Edinburg along the North Fork of the Shenandoah River and an expanded area along Stony Creek to the west of Edinburg. Formations in these areas include both the Martinsburg shale and various carbonate units.

Groundwater quality overall is very good. Exceptions to

very good quality do exist, however. Hardness and iron are found to be excessive in some sectors. Hardness is very high in the carbonate formations and somewhat less, though still "very hard", in the Martinsburg Formation. Iron concentrations are noticeably high in the Silurian and Devonian shale and sandstone formations but seldom are excessive in the carbonates and the Martinsburg Formation.

Groundwater problems are limited and infrequent but on occasion include well interference, sinkhole collapse, and local contamination caused by septic systems, agricultural runoff, and leaks and spills of petroleum products.

#### CHAPTER I

#### INTRODUCTION

#### Background

Shenandoah County is located in the northwest portion of the State (Plate 1), bounded on the west by West Virginia (Hardy County). Virginia counties forming the other boundaries are: Rockingham on the south, Page and Warren on the east, and Frederick on the north.

Formed from Frederick County in 1772, the County covers 407 square miles (324,480 acres). There are no independent cities, although there are six incorporated towns: Edinburg, Mt. Jackson, New Market, Strasburg, Toms Brook and Woodstock.

The population of Shenandoah County is 25,900, according to 1975 statistics furnished by Tayloe Murphy Institute at the University of Virginia. Projections by the Division of State Planning and Community Affairs for the year 2000 place the figure at 28,200.

Poultry is the prime source of revenue. In addition, livestock and dairy herds are increasingly important in Shenandoah County.

Present water supply is adequate, and there are no major surface- or groundwater-related problems known to exist in the County. Future water needs easily should be met through the abundant water resources present there. These resources, however, are not evenly distributed, and certain areas offer much greater groundwater potential than others due to the diversified topography and

and geology. No serious water quality problems affect the County, but the limestone terrains are conducive to groundwater pollution.

## Purpose and Scope of Report

The principal goal of this report is to acquaint the public with groundwater conditions in Shenandoah County. In addition to providing some general information about the County, this report is a compilation of previous geologic and hydrologic investigations carried out under the auspices of the State Water Control Board and other state agencies. By discussing groundwater availability, development and quality, this report is intended to serve as a reference to local government, private citizens, developers, well drilling contractors, consultants, and anyone else desirous of information relative to utilizing and protecting the groundwater resources of Shenandoah County.

## Methods of Investigation

Most of the general background and geologic information appearing in this report is a summary of previous work. Some of the information on water well construction, groundwater quality and groundwater withdrawal has been obtained from other state agencies, although the bulk of it has been collected by the State Water Control Board.

Much of the previously unpublished information on individual well construction data and quality analyses has been collected as a result of the Groundwater Act of 1973. This Act requires that a Water Well Completion Report (Form GW-2) must be submitted to

the state of the s

the Board for all wells drilled, and that owners of industrial and public water supplies submit quarterly reports (Form GW-6, Ground-water Pumpage and Use) detailing groundwater withdrawal. In addition, the Board requires that drill cutting samples be collected at 10-foot intervals on all public and industrial supply water wells and those wells which are drilled to unusual depths or are located in areas deemed deficient in geologic information.

A concentrated effort has been made over the past several months to gather information relating to quality trends in Shenandoah County. In addition to specific sampling areas, groundwater quality information is obtained from regular monthly sampling runs throughout northwestern Virginia. Domestic supplies are generally the sample targets, although some industrial supplies are checked occasionally. All of the public system quality information on file at the Board has been obtained from the Virginia Department of Health.

Another source of quality information is the Pollution Response Program (PReP), maintained by the Board for the sole purpose of responding to citizen complaints of water pollution of any type. This includes pollution of both groundwater and surface water by accidental or intentional spills of hazardous chemicals, oil, gasoline, refuse, and industrial wastes.

All well information, well completion reports and records of groundwater quality analyses cited in this report are on permanent file in the State Water Control Board Headquarters Office in Richmond and the Valley Regional Office in Bridgewater. These

data are computerized for storage and retrieval and were used to compile Appendices B and C.

## Previous Investigations

Two recent reports published by the Virginia Division of Mineral Resources offer comprehensive geologic information for about two-thirds of the County. A 1974 report by Robert S. Young and Eugene K. Rader entitled Geology of the Woodstock, Wolf Gap, Conicville, and Edinburg Quadrangles, Virginia (Report of Investigations 35, Virginia Division of Mineral Resources) and a 1976 report by Rader and Thomas H. Biggs entitled Geology of the Strasburg and Toms Brook Quadrangles, Virginia (Report of Investigations 45, Virginia Division of Mineral Resources) have been drawn upon heavily in preparing this report.

and R. H. DeKay. Cady's report, Ground-Water Resources of the Shenandoah Valley, Virginia (Bulletin 45 of the Virginia Geological Survey, 1936), is quite comprehensive and is the only major hydrologic report to incorporate virtually all of the County.

In Development of Ground-Water Supplies in Shenandoah National Park, Virginia (Mineral Resources Report 10, Virginia Division of Mineral Resources, 1972), DeKay touches lightly upon some of the groundwater resources of the Blue Ridge region. Frank Reeves discussed another aspect of the subsurface water resource in his 1932 report, Thermal Springs of Virginia (Bulletin 36, Virginia Geological Survey). The Virginia Division of Water Resources report on the Potomac-Shenandoah River Basin (Volume I and III,

1968-69) included Shenandoah County, as did Trainer and Watkins' report on <u>Geohydrologic Reconnaissance of the Upper Potomac River Basin</u> (U. S. Geological Survey Water Supply Paper 2035), published in 1975.

## Water Well Numbering System

Water Well Completion Reports are assigned a unique number by which the reported well is thereafter identified. Water quality and withdrawal information for that particular well are also identified by that number.

Each county in Virginia is assigned a three-digit county code, the code for Shenandoah County being 185. Within each county, wells are numbered sequentially and chronologically with a few exceptions. For example, a report received on a particular day might be numbered 185-16, while a report received the following day would become 185-17. All wells are assigned numbers as they are received and, therefore, appear at random throughout the summary. When citing specific wells in this report, the well number will be given without the county code.

When it is necessary to contact the Board about a particular well, it is advisable to refer to the owner (or location if more descriptive) and its well number. For example: New Market Battlefield, (185-98).

#### CHAPTER II

#### PHYSICAL SETTING

## Physiography

Shenandoah County is situated within the Valley and Ridge
Physiographic Province. This Province is characterized by alternating ridges and valleys trending in a northeast-southwest direction. The County is bounded on the east by Massanutten
Mountain and on the west by Little North Mountain, while a narrow valley separates them. The lowest point in the County, just under 500 feet above sea level, is along the North Fork of the Shenandoah River where it flows into Warren County east of Strasburg (Plate 2). The highest elevation is approximately 3300 feet on Mill Mountain along the Virginia-West Virginia border.

The northern terminus of Massanutten Mountain at Strasburg is the most prominent landform. Rising to an elevation of 2,400 feet, the blunt peak can be seen for miles. Buck Hill, rising 600 feet above the valley floor northwest of Mt. Jackson, is one of the more notable landforms in the Central Valley, second only to the famous Seven Bends of the Shenandoah River located between Edinburg and Strasburg.

Caves and caverns are abundant in the County. In addition to the commercially-operated Shenandoah Caverns and Battlefield Crystal Caverns, approximately 80 other caves are known to exist. An abundance of sinkholes, almost exclusively found in limestone regions, indicates the area is riddled with subsurface solution channels and caves, a typical feature of karst terrains.

## Drainage

Shenandoah County is located entirely within the Potomac-Shenandoah River Basin. Stretching from Highland County in the west to the Chesapeake Bay in the east, the Basin covers 5,706 square miles in Virginia alone and extends into West Virginia, Maryland, and Pennsylvania.

The North Fork of the Shenandoah River extends the length of the County and provides the principal surface drainage. Stony Creek and Cedar Creek are the two major tributaries and drain the southwest and northwest regions, respectively. Passage Creek, flowing through Fort Valley, provides drainage for the highlands of Massanutten Mountain.

## Climate

The climate of the County is characterized by mild winters and warm, humid summers. The mountainous regions and the wide range in elevation are the two major factors controlling the climate.

The average annual atmospheric temperature for the County is  $55^{\circ}$ F. Extremes have been recorded as high as  $105^{\circ}$ F in July 1954 and as low as  $-10^{\circ}$ F in January 1963. The average annual precipitation is approximately 34 inches; rainfall is the dominant precipitation factor. Summer rainfall is provided principally by showers and thunderstorms, the latter occurring on an average of 40 days. Although the average annual snowfall is around 25 inches, measurements in the last 43 years have varied from 2 inches to 65 inches.

٦.

- VRO; Soil Conservation Virginia State Water Control Board Service; Virginia Cave Survey

Table 1 lists temperature and precipitation data from the non-recording weather station at Woodstock maintained by the National Weather Service.

TABLE 1 1976 WEATHER DATA RECORDED AT WOODSTOCK, VA

Month	Average Temperatu (Degrees Fahrenhei	
January	31.8	3.90
February	44.9	0.99
March	49.2	1.61
April	56.6	1.83
May	62.0	2.61
June	72.4	2.93
July	73.3	3.16
August	71.5	1.77
September	66.0	3.55
October	51.2	10.07
November	40.6	0.82
December	33.3	1.44
TOTAL	54.40	34.68

Source: National Oceanic and Atmospheric Association

# Soils and Vegetation

Soil types can be grouped loosely into three major categories: mountainous; valley floor; and terrace and alluvial deposits. As indicated in Plate 2, better than half of the County is covered by mountainous soils. These soils are typically well to moderately-well drained and occur on ridges and steep slopes, and at the base of steep slopes in the form of colluvial materials.

Valley floor soils, which overlie limestone and shale uplands, are very rocky and usually well drained. Terrace and alluvial deposits, including flood plain material, roughly parallel the North

Fork of the Shenandoah River from the Rockingham County line to Edinburg and Stony Creek. These deposits, which are typically quite deep and well to moderately-well drained, are extremely important in the storage and transmission of groundwater. From Edinburg north to Strasburg, which includes the Seven Bends, alluvial-colluvial material does border the river but the hydrogeologically important terrace deposits are absent.

Vegetation is mainly of two types: forest lands and agricultural areas. The valley area is predominantly pasture and cropland, while close to 60 percent of Shenandoah County's 324,480 acres are forested. Approximately 35 percent of the forested area is included in the George Washington National Forest. Such major forest areas provide a shaded environment, relatively thick soil and dense undergrowth which retard surface runoff and erosion and encourage infiltration. These factors combine to make expansive woodlands an important factor in replenishing and maintaining both the groundwater and surface water resources.

#### CHAPTER III


#### **HYDROGEOLOGY**

## The Hydrologic Cycle

The close relationship between geology and the occurrence, distribution, availability and quality of groundwater makes geologic information a prerequisite to understanding the hydrogeology of an area. Topography, rock type and geologic structure are principal factors which govern the storage, transmission, yield, quality and utilization possibilities. Other elements influencing groundwater include soil, vegetation, temperature and certain works of man. Overriding most of these factors are quantity, intensity, frequency, duration and distribution of precipitation. The hydrologic cycle (Plate 3) explains the circulation of water among the oceans, air, land surface and underground.

Topography is a significant factor influencing groundwater conditions. As a general rule, low-lying areas near hills and mountainous regions should be considered as having greater groundwater potential than the higher elevations because runoff from slopes results in increased infiltration in valleys. Pervious soils, cultivated land and dense vegetation allow greater infiltration than do clayey and barren lands which are conducive to higher rates of runoff. High temperature coupled with a high degree of evaporation negatively affects groundwater recharge. In urban areas, runoff increases and infiltration diminishes due to the impermeable expanse created by paved areas and buildings.

The Hydrologic Cycle



Source: Gibson and Singer (1971)

Plate No. 3

#### Geology and Groundwater


Different types of rock vary considerably in their ability to absorb, store, and yield water. Shenandoah County is underlain by sedimentary rocks which were deposited in ancient seas. These rocks contain water in voids, bedding planes, fractures and solution channels. The predominant rock types in the County are limestone, shale, sandstone, and unconsolidated sand and gravel. For the purpose of this report, limestone, a calcium carbonate, and dolomite, a calcium-magnesium carbonate, will be termed loosely as "carbonates".

Carbonate rocks have highly variable water-bearing properties and are poor to good aquifers. Where joints have been enlarged into solution channels by the dissolving action of water, large

volumes of water may be stored and transmitted (Plates 4C and 4F). The solution action can produce openings as large as the greatest caves. Generally, it is believed that the formation of solution channels in carbonate rocks operates most actively above and immediately below the water table, where the water in the rocks contains a greater charge of carbon dioxide and circulates most vigorously. Carbonate rocks adjacent to major streams have a high potential for recharge and are relatively unaffected by seasonal water table fluctuations. Therefore, limestone and dolomite formations which outcrop near major streams may be very prolific aquifers, whereas those occurring in areas remote from major streams may produce only meager amounts of groundwater.

Shale has relatively high porosity, but permeability is very low. Poor to sometimes fair quantities of water may be obtained from pore spaces, joints, bedding planes and shaley partings, but shale generally forms an aquiclude, or barrier, confining groundwater to underlying aquifers. Clay has hydrologic properties similar to those of shale and is relatively impermeable; i.e., incapable of supplying water to wells.

Sandstone contains water in pore spaces which are dependent on sorting, grain size, shape, packing and, most importantly, degree of cementation (Plate 4E). Sandstone cemented with soluble calcite or unstable clay minerals may break down easily and develop high permeability. Some calcareous sandstone formations are excellent aquifers, but a sandstone cemented with silica may have practically no permeability unless fractured.



Source: Meinzer (1923)

PLATE NO. 4

Unconsolidated sand and gravel in alluvial and terrace deposits are highly porous and permeable and usually occupy areas favorable for groundwater recharge (Plates 4A, 4B and 4D). Sand and gravel beds lying adjacent to, and below the level of, a major stream often yield abundant supplies of groundwater, while sand and gravel in deep strata are also good aquifers. Similar deposits at higher elevations may contain little groundwater.

Igneous and metamorphic rocks have very low porosity and permeability. However, small supplies of water generally are available near the surface where weathering has partially decomposed the rocks. Below the weathered zone small quantities of water may occur in fractures and along contacts between different rock types.


Geologic structure may strongly influence the occurrence of

groundwater, and this is especially true in certain areas of Shenandoah County. Anticlines (up-folds in the rock strata) may bring good water-bearing beds near the surface along their axes and bury them along the flanks (Plate 5A). Similarly, synclines (down-folds in rock beds) may bring water-bearing units near the surface on the flanks or may cause them to descend to great depths along the axis (Plate 5B). The axial portion of a syncline can act as a collection area and, if tapped, may yield significant quantities of water under high pressure. Water may flow under its own pressure to, or above, the land surface, and when this occurs, the well is termed "artesian". Similarly, excellent groundwater storage potential exists along well-fractured anticlinal axes, but water pressure is generally not sufficient to cause artesian conditions.


Faults are fracture zones along which there has been displacement of rock masses relative to one another, and they often parallel folding. The associated fracture openings in soluble rocks may be enlarged by the solution action of groundwater, thereby resulting in high well yields. Well yields from carbonate rocks are directly influenced by the size and number of fractures intersected (Plate 6). Faulting can also be detrimental to the groundwater potential of an area. Not only can it act as a collection zone for groundwater through its higher permeability, but it may also serve as a barrier to limit groundwater movement by causing the dislocation of a water-bearing formation.

Joints are fractures along which there has been no appreciable movement. They are favorable to groundwater occurrence, but, like

## STRUCTURAL INFLUENCES IN GROUNDWATER AVAILABILITY




A. An anticline may bring a water-bearing rock bed near the surface at its axis or send it to great depths along its flanks.



B. A syncline may bring a water-bearing rock bed near the surface at its flanks or bury it at its axis.

Source: Virginia State Water Control Board - VRO

**PLATE NO. 5** 



faults and other fractures, tend to become fewer and smaller with depth.

# Hydrogeology of Shenandoah County

This County is composed entirely of sedimentary rocks occurring in relatively narrow northeast-southwest belts. These rocks have been heavily folded, and three major faults are present. Geologic and groundwater conditions of the area are illustrated in Plate 7.

<u>Geologic Setting</u>. The oldest rocks in Shenandoah County are those of Cambrian and Ordovician age (600-425 million years old). Exposed along the floor of the Shenandoah Valley, these limestone

and dolomite formations were deposited when crustal downwarping caused a long, narrow trough to form in a northeast-southwest direction, generally coinciding with the present location of the Appalachian Mountain Range from Alabama to Newfoundland. This huge depression was invaded repeatedly by seas and served as a depositional site for thousands of feet of sediments over millions of years. During the Silurian, Devonian and Mississippian ages (425-300 million years ago) when uplift caused the sea to retreat, there was rapid erosion resulting in transport of clastic sediments into the depositional trough. These sediments later were consolidated into the younger shale and sandstone units predominating in Massanutten Mountain and from Little North Mountain west to the state line.

Following this long depositional and uplift period, the area was subjected to horizontal forces from the southeast which folded the rocks into a series of anticlines and synclines and, in some places, displaced huge masses of rock for thousands of feet along fault planes. Erosion and terrestrial deposition over the last 300 million years has altered the land surface to its present topography. The more resistant rocks, such as sandstone and quartzite, form the ridges while the less resistant shale and limestone units have been eroded to form the valleys.

The youngest deposits, less than two million years old, are the terraces and flood-plain alluvium which occur in proximity to the major streams. These materials have been deposited by the action of floods and consist mainly of sand and gravel.



Geologic Formations and Groundwater Occurrence. The occurrence, lithology, and average thickness of the formations discussed above are detailed in the following paragraphs as a prelude to discussing groundwater occurrence and availability in Shenandoah County. Nomenclature is consistent with that used by Young and Rader (1974) and by Rader and Biggs (1976).

Groundwater conditions vary considerably across the County due to the diverse geology and topography. Carbonate formations are typically considered to be the best aquifers in the Valley and Ridge Province in Virginia, but the Ordovician-aged Martinsburg shale is considered to be the best groundwater producer in Shenan-doah County. This unusual situation is explained in part by the presence of Smith's Creek and the North Fork of the Shenandoah River which traverse the formation throughout much of their courses in this County. The Cambro-Ordovician carbonates are very good producers, though not generally as prolific as the Martinsburg Formation. The Silurian and Devonian shale and sandstone units in Massanutten Mountain and the upland region west of, and including, Little North Mountain exhibit only poor to moderate potential for groundwater.

Cambrian units (600-500 million years old) consist of a thick series of dolomite and limestone with a few thin units of sandstone and shale. Two major and hydrogeologically significant belts of Conococheague outcrop through the County; Elbrook occurrences are few and very insignificant from a hydrogeologic standpoint, with the exception of those areas where alluvial and terrace deposits

overlie the unit between Elkton and Grottoes.

The Ordovician-aged (500-425 million years old) Beekmantown, Edinburg, and Martinsburg Formations are the three principal units which, along with the Conococheague (Cambrian age), comprise the bulk of the central lowlands floor. In Shenandoah County, the Beekmantown is basically a dolomite unit but does contain major limestone zones; the Edinburg is a limestone, and the Martinsburg is a shale. The Martinsburg, with a thickness of possibly 3000 feet, is one of the most persistent formations in the Shenandoah Valley and occurs mainly in a three-mile belt extending the length of the County along the base of Massanutten Mountain. Rader and Biggs (1976) indicate limestone beds are present in the Martinsburg in the Massanutten Synclinorium.

The Silurian rocks (425-405 million years old) consist of a moderately-thick series of sandstones and shales. Silurian sandstone is highly resistant to weathering and is one of the principal ridge-formers in the Appalachian Mountains. It is these sandstone formations which support the Massanutten range and the ridges along the County's western border.

Devonian shales and sandstones (405-345 million years old) occur in three major areas within the County. Two extensive belts west of Little North Mountain and a large portion of Massanutten Mountain are represented by these units. Although they represent approximately one-third of the County's 507 square miles, they are very insignificant hydrogeologically.

Quaternary materials (2 million years old-present) represent

the youngest deposits in the County. They are mainly flood-plain alluvium and terrace deposits above the flood plains that represent former levels of the major streams, notably the North Fork of the Shenandoah River. These deposits consist of gravel, sand, silt, and clay.

Geologic Structure. Of the many structural features present in Shenandoah County, two folded features and two faults appear to be primarily responsible for the overall structure of the area. Two major synclinal structures roughly follow the east and west borders of the County: The Massanutten Synclinorium and the Supin Lick Syncline, respectively. On the flanks of the Supin Lick Syncline sandstone and shale formations of Devonian age crop out west of Little North Mountain. The Massanutten Syncline is basically a very large trough which extends far beyond the County's northern and southern borders and includes Massanutten Mountain. This fold and its related minor structures are responsible for the wide expanse of Martinsburg shale present along the western base of Massanutten Mountain.

North Mountain Fault is the major zone of displacement and runs the length of the County. Older Cambrian carbonate units have been thrust over Ordovician, Silurian, and Devonian rocks, mostly shale and sandstone. Thick shattered zones are present where carbonate rocks have been involved in crushing due to fault activity, a phenomenon which greatly influences groundwater potential in the area.

The Saumsville Fault extends from a point approximately four

miles due north of Woodstock to approximately the Rockingham County line in the southwest. Displacement involves the carbonate rocks along the valley floor and generally results in older carbonates being thrust over younger carbonates.

These structural features directly influence groundwater conditions. The Massanutten Synclinorium serves as a large runoff collection area to recharge the Martinsburg shale belt and the overlying alluvial materials along the west toe of the Massanutten Range. The Supin Lick Syncline performs the same function, though the units of which it is formed offer less potential for groundwater storage and movement. Extensive fracturing likely has occurred along the two major fault zones identified above, thus facilitating infiltration and groundwater occurrence.

Table 2 summarizes the major geologic units of Shenandoah County, including their water-bearing properties. Groundwater potential of the various geologic formations underlying the County will be elaborated upon in the next chapter.

## Groundwater Movement and Storage

While there have been no detailed studies conducted of ground-water movement and storage in Shenandoah County, it is recognized that a very close relationship exists between surface water and groundwater. Groundwater movement and storage are influenced by topography, rock type, and geologic structure, and movement is generally in the same direction as surface runoff, only much slower. Movement and storage patterns are distinctly different in alluvial deposits, carbonate rocks, and shale/sandstone units.

TABLE 2

GEOLOGIC FORMATIONS AND THEIR WATER-BEARING PROPERTIES SHENANDOAH COUNTY\*

Water-Bearing Properties	Good to excellent, especially when underlain by carbonate rocks	Poor Poor	Poor Poor	Poor Poor	Poor Poor
Character	Sand, clay, gravel	Shale, sandstone Shale, sandstone	Shale, sandstone Shale, sandstone Shale Shale	Sandstone Quartzite Sandstone, quartzite	Sandstone, shale Sandstone, shale
Symbol	Qsg	Dch Dch	Dha Dhar D	Dri Stu Sm	0j 0os
Formation	Alluvial and terrace deposits	Hampshire Chemung	Brallier Mahantango Marcellus Needmore	Ridgeley Tuscarora Massanutten	Juniata Oswego
Age (Million Years)	2-present		405-345	425-405	500-425
System	Quaternary		Devonian	Silurian	Ordovician

TABLE 2 (Continued)

GEOLOGIC FORMATIONS AND THEIR WATER-BEARING PROPERTIES SHENANDOAH COUNTY\*

System	Age (Million Years)	Formation	Symbo 1	Character	Water-Bearing Properties
		Martinsburg	Omb	Shale; some sandstone, limestone	Fair to good; generally good along west toe of Massanutten Range
7	7000	Oranda	00e	Siltstone with limestone	Fair to good
Urdovician	200-423	Edinburg	00e	Limestone	Fair to good
		Lincolnshire	01	Limestone, chert	Fair
		New Market	0u	Limestone	Fair
		Beekmantown	90	Dolomite, chert	Fair to good
		Stonehenge	0st	Limestone	Fair to good
omby.	009-009	Conococheague	000	Limestone, dolomite	Fair to good
		Elkbrook	Ce	Limestone, dolomite	Fair to good

\*Modified after Young and Rader (1974) and Rader and Biggs (1976)

Source: Virginia Division of Mineral Resources; Virginia State Water Control Board - VRO Movement. Elevation is the prime factor determining ground-water movement in alluvial deposits. When the water table is at a higher elevation than a stream bed, groundwater will move toward the stream, thus maintaining surface flow during dry periods. During those times of year in late summer and early fall when the water table generally drops, conditions may reverse, resulting in seepage of water from the stream into the alluvium.

Groundwater movement within the thinly-covered carbonate rocks underlying the central portion of the County is more complex. Some of the carbonates are very dense and resistant to the dissolving action of water while others commonly contain countless fractures and solution cavities and provide for rapid movement and abundant storage of groundwater. The unpredictable size, shape, and direction of solution cavities makes groundwater movement very complicated in the carbonates. Where highly-fractured carbonates occur at or near the surface, optimal conditions exist for surface runoff and infiltration to enter into underground solution channels. Quite often a single sinkhole serves as a major infiltration point for groundwater recharge. Once water enters solution cavity systems, it behaves much in the same manner as surface streams and may discharge some distance away as a spring. Sometimes an entire stream may disappear in carbonate rocks and emerge as a large spring many miles away, thus giving rise to such names as Sinking Creek or Lost River. However, there are no known examples of this situation in Shenandoah County.

Groundwater movement in the shale/sandstone areas of the

western part of the County and Massanutten Mountain is relatively simple. Water infiltrates the rock until it intersects bedding planes and then flows down-dip. Very few fractures are found in shale, so movement patterns are directly controlled by structure.

Storage. Maximum groundwater storage is possible in the alluvial and terrace deposits bordering major streams. These deposits consist mainly of non-cemented coarse sands, gravels and boulders which provide maximum voids. The most important groundwater storage area in this County is the alluvium bordering the North Fork of the Shenandoah River. Other notable examples are along Smith's Creek in the southeast and along Stony Creek from Jerome to Edinburg.

Where the flood-plain deposits overlie carbonate rocks with abundant solution cavities, groundwater conditions are considerably enhanced. Permeable flood-plain deposits minimize runoff and increase rates of infiltration. Not only do these deposits provide for storage at shallow depths, but deeper wells can often tap abundant supplies stored in the cavernous bedrock which will likely be saturated due to the water storage and transmission properties of the overlying material.

Storage capacity in carbonate rocks depends, as with movement, on the rocks' resistance to the dissolving action of water. Large solution voids sometimes act as reservoirs, and fractures resulting from structural activity can contain vast amounts of water.

Shale formations, as well as most sandstone units, seldom afford adequate groundwater storage. An exception in Shenandoah County,

however, is the Martinsburg shale which covers one-third of the valley floor and outcrops along the large Massanutten Synclinorium. Four factors combine to make the Martinsburg a good groundwater producer in Shenandoah County: 1) high recharge potential from the western slopes of Massanutten Mountain; 2) extensive alluvial and terrace deposits overlying the formation along Smith's Creek and the North Fork of the Shenandoah River; 3) the synclinal (trough) structure; and 4) minor limestone beds and the highly calcareous nature of the shale.

Shale and sandstone units comprising Massanutten Mountain and the Little North Mountain sector are more typical and are considered relatively poor groundwater sources. Steep slopes and high runoff rates may render the beds unlikely to collect very great quantities of infiltered water, making them adequate only for the development of small-scale domestic supplies.

en en la companya de la co

#### CHAPTER IV

### GROUNDWATER POTENTIAL AND DEVELOPMENT

## Groundwater Potential

The groundwater potential of an area is the ability of that area to yield groundwater. Potential is determined mainly by the geologic setting (rock type and structure) and topography. Geologic setting is the overriding factor in Shenandoah County. Once the geology has been determined, then topographic setting may be an important secondary consideration, especially in the highland areas in the east and west. Plate 8 illustrates the three major groundwater potential categories occurring in Shenandoah County. The map is based on the occurrence of geologic formations and their general water-bearing characteristics. The map is of a general nature, and exceptions will normally occur in each category.

Terrace and Alluvial Deposits. The terrace and alluvial deposits and the underlying carbonate and shale formations afford the greatest groundwater potential to be realized in Shenandoah County. The terraces are step-like and are formed mostly of sand and gravel deposited by the stream as it flowed at higher elevations in the past. The alluviual deposits are formed mostly of clay and silt and border practically every stream in the County.

Young and Rader (1974) note that the ancestral North Fork of the Shenandoah River was responsible for the deposition of the terraces. They have identified three levels of terrace and indicate that the upper level alone is at least 160 feet thick and two miles in lateral extent. They are capable of storing and transmitting large quantities of water and act as a recharge mechanism for the underlying formations. Water table conditions are fairly uniform throughout the deposits, and excellent well yields may be developed at fairly shallow depths.

The bulk of terrace and alluvial deposits overlie the Conococheague, Beekmantown, Oranda and Edinburg carbonates and the Martinsburg shale. The most significant areas of terrace deposition include a belt extending from New Market to Edinburg and an expansive area fanning out along Stony Creek to the west from Edinburg. Several smaller terrace areas are located to the north and southwest of Edinburg. Minor alluvial deposits border the North Fork of the Shenandoah River extending from Edinburg north to Strasburg, and some terrace deposits are present at Strasburg.

Structural deformation in the form of the Saumsville Fault, a major fault zone, and alternating anticlines and synclines offer increased fractures and associated solution activity to enhance groundwater storage and transmission in the area west of Edinburg. Less severe deformation has occurred south of Edinburg; the Mt. Jackson Anticline is the most notable phenomenon.

<u>Cambro-Ordovician Formations</u>. The Cambro-Ordovician formations not influenced by terrace and alluvial deposits have far less potential than their counterparts. These rocks include both the carbonate formations and the Martinsburg formation, and although fair to good yields are generally available, topographic setting plays a

• . 

much more important role in determining the success of a well.

Potential is more dependent on surface water recharge from higher elevations since there are no overyling saturated deposits.

Marin Average Con-

The carbonate beds exhibit several major fault zones and assorted anticlines and synclines which offer extensive areas of fracturing. Potential generally increases with greater proximity to rivers and streams, since solution activity is accelerated and streams provide a source of recharge. Solution activity is widespread throughout all the carbonate beds as attested to by numerous caves and sinkholes.

The Martinsburg Formation appears to offer potential nearly equal to that of the carbonate formations. Though this is the exception rather than the rule, several factors combine to create this condition.

The largest and most prolific water-bearing exposure is located along the western toe of the Massanutten Range where it is traversed for much of its length by the North Fork of the Shenandoah River. The stream undoubtedly is an important recharge mechanism, and potential is further influenced by surface runoff from the steep western slopes of Massanutten Mountain. The Short Mountain Syncline, a large bowl-shaped structure just west of Massanutten Mountain, is occupied almost entirely by the Martinsburg Formation. The syncline acts as a large groundwater collection area which further enhances the groundwater potential.

Two minor western exposures of the Martinsburg also offer good groundwater potential though conditions are not conducive to the

existence of the larger reserves commonly available from the exposure at the base of the Massanutten Range. Faulting in these areas, coupled with mountainous recharge areas, likely contribute to the potential of these exposures.

Silurian and Devonian Shale and Sandstone Formations. This series of formations comprises the Massanutten Range and the mountains in the western part of the County. Groundwater potential is not as great as that found in the other aquifer systems, yet the area has greater potential than is normally found in corresponding rock types of other areas. The rock units of the western mountainous area appear to offer higher groundwater potential than do the units comprising Massanutten Mountain. This is likely due to the extensive folding which has taken place west of the North Mountain Fault, whereas local deformation in the Massanutten Range proper appears to have been significantly less.

## Groundwater Development

Groundwater is the principal source of water supply for Shenan-doah County. The towns of Edinburg, Mt. Jackson, New Market and Toms Brook utilize groundwater wholly or in part for their water supplies. Only two towns, Woodstock and Strasburg, are supplied by surface water, and the back-up system for Strasburg is a groundwater source.

Projections based on population and housing statistics supplied by the Division of State Planning and Community Affairs (1972) indicate that approximately 49 percent of the County's population is served by groundwater. The remaining portion is supplied either by surface water or cisterns. Based on this percentage and on public and industrial pumpage information on file, total daily groundwater pumpage is estimated to be in excess of three million gallons per day (MGD). Industrial usage is somewhat less than 1 MGD, and public usage is approximately 1 MGD. Total domestic demand, including commercial and institutional users, is estimated to be approximately 1.5 MGD.

Groundwater development is confined mainly to the Central Valley area. Data on file indicates the three carbonate formations have been developed to the greatest extent. The Martinsburg Formation, though a very important water-bearing unit, has not been developed nearly as much as the carbonates. The Silurian and Devonian units have seen very limited development with the exception of the Bryce Mountain Resort area at Basye. Table 3 lists depth-yield relationships for the three aquifer systems. It is important to note that even though the table indicates the Silurian and Devonian units are very good groundwater producers, almost all the data available are from the Basye area which has to date proved to be an exceptional area considering the rock type.

Plate 9 shows groundwater development based on data currently on file. Though there are exceptions in each category, this presents a general picture of current development trends.

Public Systems. A public system is defined by the Virginia

Department of Health (1974) as one which distributes water to more
than 25 individuals or more than 15 connections. At present there

TABLE 3

AVERAGE YIELD (GPM) BY WELL DEPTH
FOR THE AQUIFER SYSTEMS OF SHENANDOAH COUNTY\*

			Depth	(ft)		1
<u>Aquifer</u>	0-99	100-199	200-299	300-399	400-499	Below 500
Carbonate Minimum Maximum Median	(5) 8 20 12	(45) 1 220 26	(42) 1 160 29	(22) 2 205 36	(19) 2 400 70	(18) 1 100 24
Martinsburg Minimum Maximum Median	(9) 6 50 22	(24) 3 183 33	(8) 2 275 51	(2) 6 31 19	(7) 3 200 44	(3) 11 450 160
Silurian/ Devonian Minimum Maximum Median	(8) 12 60 24	(14) 4 80 19	(2) 5 20 13	(5) 2 90 43	(4) 22 38 29	(5) 1 7 4

<sup>\*</sup>All yields rounded to nearest gpm; parentheses () indicate number of wells used in making calculation
Source: Virginia State Water Control Board - VRO

are 31 public systems in Shenandoah County supplied by groundwater.

Table 4 lists public users for which information is available.

(Note: Table 4 does not include public systems supplying industries.

These systems are included in the section covering industrial systems).

The majority of these public systems have been developed in the Central Valley area. A few of the systems, most notably the Stoney Creek Utilities Corporation which serves the Bryce Mountain Resort area, have been developed in the Silurian/Devonian shale and sandstone formations. Available well data for most public systems is incomplete.

,

TABLE 4
PUBLIC GROUNDWATER SYSTEMS IN SHENANDOAH COUNTY

System	Average Pumpage (GPD)
Battleground Trailer Park	8,500*
Blue Ridge Homes (Section 2)	9,000*
Blue Ridge Trailer Court	6,800*
Borden's Trailer Park	8,000*
Concord Mobile Homes	28,800
Edinburg (Town of)	338,530
Heishman's Trailer Park	9,000*
Holler Subdivision #2	16,000*
Lambert Mobile Home Park	86,400**
Massanutten Heights	3,600*
Massanutten View	5,000*
Mountain Run	16,000*
Mountain View	3,000*
Mountain Water Works	5,440
Mount Jackson (Town of)	169,254
New Market (Town of)	250,000
New Market Battlefield	516
Round Hill Trailer Park	2,500*
Ryman's Subdivision	4,000*
Stoney Creek Utilities	15,938
Sundance Mountain Subdivision	8,000*
Toms Brook-Maurertown Service Authority	
Westbrook Subdivision	2,500*
TOTAL	1,043,649

<sup>\*</sup>Normal production figures supplied by Virginia Department of Health \*\*Maximum production figures supplied by Virginia Department of Health

Source: Virginia Department of Health; Virginia State Water Control Board - VRO

Industrial Systems. Industrial systems probably account for less than 1 MGD of groundwater withdrawal in Shenandoah County. Though some industrial systems are actually classified as public systems because one or more wells or springs may supply "sanitary" water, for the purposes of this report they are included as industrial systems. Major industrial users for which data are available are listed in Table 5.

TABLE 5

MAJOR INDUSTRIAL GROUNDWATER USERS IN SHENANDOAH COUNTY\*

Industry	Average	Pumpage	(GPD)
Aileen (Edinburg)		8,000	
Aileen (Woodstock)	e e e	3,000	
Bowman Apple Products		20,000	
Chemstone		25,797	
Howell Metal Co.		86,400	
Irvin Candy Co.		2,000	. "
Johns-Manville		6,274	
Rocco Farm Foods		495,000	
Shenandoah Block		4,250	
	TOTAL	650,721	

<sup>\*</sup>Includes some systems actually classified "Public" by the Virginia Department of Health

Source: Virginia State Water Control Board - VRO

Statistics derived from data on file indicate that the average industrial well in this County is 378 feet deep and yields 97 gpm. Table 6 elaborates further on these figures. The majority of these wells have been developed in the carbonate formations; only two tap the Martinsburg Formation and none have been drilled in the Silurian/Devonian formations.

TABLE 6
INDUSTRIAL WELL STATISTICS, SHENANDOAH COUNTY\*

	Depth (ft)	Yield (gpm)
Minimum Maximum	146 700	12 400
Median	378	97

<sup>\*</sup>Calculations based on records for 15 wells

Source: Virginia State Water Control Board - VRO

The four most prolific industrial wells (yields of 100 gpm or greater) have been developed in terrace and alluvial deposits overlying carbonate formations. Two wells (29 and 79) owned by Rocco Farm Foods in Columbia Furnace produce 393 and 400 gpm, respectively, from the Beekmantown Formation which is overlain by alluvial deposits bordering Stony Creek. Two wells (32 and 34) at the Bowman Apple Products Company in Mt. Jackson produce 100 and 220 gpm, respectively. These wells tap the Conococheague Formation which is recharged by overlying terrace deposits.

High-yield industrial wells generally have large-diameter casing. Wells with 20-inch casing are common, but usually the casing telescopes down to 12-, 10-, or 8-inch diameter at the bottom.

Domestic Wells. Domestic wells, including commercial and institutional wells, are numerous in Shenandoah County and are the most important source of water for the rural areas. Statistics indicate that 77 percent of the domestic wells on file yield 25 gpm or less. Only seven percent produce greater than 50 gpm. This does not necessarily indicate that higher yields are not available. Rather, it indicates that the majority of domestic needs are met with yields falling within the 25 gpm bracket, so further development is not necessary. This is further illustrated by the fact that the average domestic well in Shenandoah County is 241 feet deep (based on 238 wells) whereas the average industrial well is 378 feet deep (based on 15 wells).

## Groundwater Development Problems

Invariably some problems do arise in Shenandoah County during

the process of developing and maintaining a well system. Most of the problems are experienced in the carbonate rock areas and are directly related to solution channels.

Well Interference. Well interference in carbonate rock occurs when two or more wells tap interconnected solution channels. This causes no problem if the channel transmits a greater volume of water than all the wells can pump. However, if the volume is only enough for an adequate supply for one well, the result can be lowered levels in one or all wells. Lowered levels result in less available water, and occasionally levels drop below pump settings and cause wells to cease production altogether. Extended periods of dry weather tend to aggravate these conditions, since groundwater storage is likely to be reduced. Well interference can usually be avoided by not drilling adjacent to existing wells. Several cases of well interference have been reported in Shenandoah County, especially during periods of extended drought.

Sinkhole Collapse. A gradual, and sometimes sudden, settling of the land surface may result from over-development of the ground-water resources of an area. Accelerated solution activity in karst regions due to groundwater withdrawal often results in collapse of the land surface. Most often the collapse involves a relatively small area (less than 50 feet) and creates a sinkhole. Occasionally a subterranean stream may be revealed. Sinkhole collapse is usually the result of "underground erosion". A recent collapse in the north bound lane of Interstate 81 just south of the Edinburg exchange is

a typical karst collapse phenonemon, though it is not known if the collapse was a direct result of groundwater withdrawal.

Mud Seams. A mud seam is a solution channel that is wholly or partially filled with mud. Mud seams are quite frequently encountered in drilling operations in Shenandoah County. Continuous pumping after tapping a mud seam will sometimes remove all the mud, though it may take several hours or even days to clear the water. In most cases, however, the seam must be cased off or the well abandoned.

en en la companya de la co

### CHAPTER V

## GROUNDWATER QUALITY

## Introduction

The quality of groundwater refers to its chemical, physical and biological characteristics. Groundwater contains dissolved mineral matter, has physical characteristics such as temperature, taste and odor, and may contain bacterial organisms. These factors are controlled in part by atmospheric gases, weathering and erosion of rock and soil, and the activities of man. Groundwater quality is highly influenced by the nature of the rock and soil with which it comes in contact since temperature, pressure and duration of contact determine the amount of dissolved minerals it contains.

Soil is nature's most efficient system of filtering water. Water infiltrating through thick soil cover stands an excellent chance of being purged of its harmful constituents or having them reduced to harmless concentrations. However, in areas where rock is exposed at the land surface, particularly in carbonate regions where the rock is prone to fracturing and solution activity, the water is introduced directly into the groundwater regime without the benefit of filtering. Lacking this cleansing action, it may carry chemical and biological pollutants which are capable of degrading the groundwater resources of an entire area.

More than 60 constituents and properties frequently are included in groundwater quality analyses. Many can be highly toxic and extreme health hazards, some are undesirable yet harmless unless in very unusual concentrations, and others are

necessary for bodily functions and general good health. Constituents such as arsenic, cadmium, chromium, cyanide, mercury and lead are extremely toxic, while others such as copper, iron, manganese and zinc are generally only a nuisance but may be hazardous in large concentrations. Any groundwater supply intended for drinking purposes should be analyzed by the Virginia Department of Health.

Table 7 is a summary of common quality parameters, their recommended limits, and hazards and benefits associated with them.

## Groundwater Quality by Hydrogeologic Area

Two distinct groundwater quality trends emerge in Shenandoah County. Part of the County exhibits high hardness trends and normal iron concentrations, while the other sector has notably high iron concentrations but has minimal hardness. Plates 10 and 11 delineate general trends for hardness and iron, respectively, based mainly on geologic conditions and in part on available laboratory data. The County as a whole exhibits no major quality problems.

Table 8 is a comparison of common quality parameters for the three hydrogeologic areas.

Central Valley Area. This area encompasses two hydrogeologic units: the Cambro-Ordovician carbonate formations and the Martinsburg Formation. While these two units are similar in many respects, significant quality differences do exist. The greatest variations occur for hardness, iron and manganese.

Groundwater in the Cambro-Ordovician carbonates is more highly mineralized than that found in the other hydrogeologic units. Total

TARLE 7

### GROUNDWATER QUALITY PARAMETERS

Substance	Maximum Recommended Concentration (mg/l)*	Remarks
Bicarbonate	150	Seldom considered detrimental; lower amounts recommended for washing
Calcium	200	Seldom a health concern; may be a disadvantage in washing, laundry, bathing; encrustations on utensils
Chloride	**250 (Esthetics)	Taste is a major criterion; generally not harmful unless in very high concentrations, but may be injurious to sufferers of heart and kidney diseases; sea water is 19,000 mg/l
Fluoride	**1.4 (Health)	Presence of about 1.0 mg/l may be more beneficial than detrimental; below 0.8 mg/l may cause mottling of teeth; extreme doses (4 grams) may cause death
Hardness (as CaCO <sub>3</sub> )	0-60 Soft 61-120 Mod. Hard 121-180 Hard Above 180 Very Hard	Hard waters have had no demonstrable harmful effects upon the health of consumers; major detrimental effect is economicvalues above 100 mg/1 become increasingly inconvenient; wastes soap and causes utensil encrustation
Iron	**0.3 (Esthetics)	Essential to nutrition and not detrimental to health unless in concentrations of several milligrams; main problems are bad taste, staining and discoloration of laundry and porcelain fixtures
Magnesium	150	Not a health hazard because taste becomes extremely unpleasant before toxic concentrations reached; may have laxative effect on new users
Manganese	**0.5 (Esthetics)	Essential to nutrition but may be toxic in high concentrations; taste becomes problem before toxic concentrations reached; undesirable because it causes bad taste, deposits on cooked food, stains and discolors laundry and plumbing fixtures
Nitrate	**10 as N, 45 as NO <sub>3</sub> (Appendix B listed as NO <sub>3</sub> , Health Department as N) (Health)	May be extremely poisonous in high concentrations; may cause disease in infants ("blue baby"); irritates bladder and gastrointestinal tract, may cause diarrhea
рН	5.5-8.0	Indicates whether solution will act as an acid or base; water acquires "sour" taste below 4; high values favor corrosion control; efficiency of chlorination severely reduced when pH above 7
Potassium	1000-2000	May act as a laxative in excessive quantities
Sodium	100	May be harmful to sufferers of cardiac, circulatory, or kidney disease; concentrations as low as 200 mg/l may be injurious
Solids (Total Dissolved)	500	Not a health hazard above 500 mg/l, but may impart disagreeable taste, corrode pipes; general indicator of how highly water is mineralized
Specific Conductivity	1000	An indicator of the amount of dissolved solids in water; high concentrations can cause corrosion of iron and steel
Sulfate	**250 (Esthetics)	Above 250 $\ensuremath{mg/l}$ may act as laxative on new users; may impart foul taste and odor

 $<sup>{\</sup>tt *Recommended}$  concentrations based on current literature

Source: McKee and Wolf (1963); Virginia Department of Health

<sup>\*\*</sup>Actual limits established by the Virginia Department of Health; parentheses () indicate basis for limit

TABLE 8

GROUNDWATER QUALITY PARAMETERS:
AVERAGE VALUES (MG/L) BY HYDROGEOLOGIC AREA, SHENANDOAH COUNTY\*

Parameter	<u>Centra</u> Carbonates	l Valley Martinsburg	Western Highlands and Massanutten Range
Calcium Minimum Maximum Median	(39) 8.80 175.00 78.83	(15) 24.00 196.00 80.67	9.00 56.00 26.75
Hardness (Ca-Mg) Minimum Maximum Median	(38) 131.00 595.00 309.08	(15) 112.00 550.00 255.53	(11) 32.00 191.00 103.91
Iron Minimum Maximum Median	(35) 0.00 4.00 0.14	0.00 1.80 0.35	(11) 0.00 6.20 2.07
Magnesium Minimum Maximum Median	(39) 2.30 66.00 28.16	(15) 3.50 37.20 14.57	(11) 2.40 17.30 10.22
Manganese Minimum Maximum Median	0.00 0.20 0.05	0.00 0.51 0.16	(10) 0.00 2.00 0.38
Nitrate (as NO <sub>3</sub> ) Minimum Maximum Median	0.00 50.90 15.34	0.00 28.80 6.15	(9) 0.00 1.30 0.33
pH Minimum Maximum Median	7.00 8.70 7.52	(17) 6.50 8.30 7.28	(11) 6.30 7.90 7.24
Solids (Total Dissolve Minimum Maximum Median	d)(38) 172.00 711.00 349.03	(16) 169.00 1186.00 339.19	(11) 61.00 440.00 186.09

<sup>\*</sup>Parentheses () indicate number of wells used in making calculations

Source: Virginia State Water Control Board - VRO

			-
1, 3		v , v , v , v , v , v , v , v , v , v ,	

PLATE NO. 11

1 . • s y

A-3

PLATE NO. A-1

 $\epsilon_{i}$  ,  $\epsilon_{i}$ 

dissolved solids average around 350 milligrams/liter (mg/1), but some areas tend to exhibit unusually high concentrations. Well (57) southwest of Strasburg has the highest concentration reported in the carbonates at 711 mg/1, but concentrations greater than 500 mg/1 have been detected at several locations along the major thoroughfares (U.S. Route 11 and State Route 42). Hardness averages above 300 mg/1; values in excess of 400 mg/1 are prevalent in the Strasburg and Columbia Furnace areas. Manganese is unusually high in the northern section of Strasburg but is not considered a problem in any of the carbonate formations.

Iron, chloride and sulfate trends are well below accepted standards. The Toms Brook Highway Shop well (57) has a chloride value of 90 mg/l, twice as high as any other well in the County. This unusually high concentration has been attributed to the storage of highway de-icing salts at the installation.

The Martinsburg Formation exhibits quality characteristics similar to the carbonates with a few exceptions. Total mineral matter is nearly identical, but hardness is somewhat lower at approximately 255 mg/l; the water, however, is still considered very hard. The major differences are in iron and manganese, both being found in greater concentrations in the Martinsburg. Iron averages 0.35 mg/l, just above the 0.3 mg/l drinking water limit established by the Virginia Department of Health. Manganese averages in excess of 0.15 mg/l which is above the 0.05 mg/l limit imposed by the Health Department. The high iron and manganese concentrations do not appear to be isolated to any particular area.

Western Highlands and The Massanutten Range. The groundwater encountered in these hydrogeologic areas is generally of excellent quality with the exception of iron and manganese concentrations. Iron, on the average, has been measured in excess of 2 mg/l, far above the 0.3 mg/l limit established by the Virginia Department of Health. Concentrations as high as 6.2 mg/l in well (134) and 2.9 mg/l in well (156) have been detected approximately one mile west of Conicville; well (142) just south of Orkney Springs was recorded at 3.7 mg/l.

Manganese concentrations average nearly 0.4 mg/l, eight times the Virginia Department of Health drinking water limit of 0.05 mg/l. Wells (134) and (156) west of Conicville showed concentrations of 1.25 mg/l and 0.41 mg/l, respectively. Manganese of 0.44 mg/l was detected in well (112) two miles west of Columbia Furnace.

Iron in excess of 1.2 mg/l and manganese of 0.32 mg/l has been detected in wells (74) and (75) located in Fort Valley. At present this is the only quality data on file for the Massanutten Range in Shenandoah County.

Other groundwater quality parameter concentrations have proved to be far below those encountered in the Central Valley. Total dissolved solids are approximately one-half the concentration noted in the carbonates and the Martinsburg Formation, averaging approximately 185 mg/l, and hardness is comparatively low at approximately 100 mg/l. Sulfate values are surprisingly low (7 mg/l) for the rocks involved (principally shale), but only three analyses are available for this parameter.


## Groundwater Contamination

Groundwater contamination occurs when foreign matter of any nature enters the groundwater system and alters the natural quality. Pollution of a groundwater supply is far more serious than surface water pollution because there is no way to purify an aquifer system. All purification must be done on an individual basis.

Methods of Contamination. The most common groundwater contamination mechanisms in Shenandoah County involve the introduction of contaminants into solution channels via sinkholes and bedrock exposures at the surface. For this reason the areas underlain by carbonate bedrock are highly susceptible to contamination.

Sinkholes are a major threat because people tend to use these depressions in the land surface for the disposal of dead animals, trash and other wastes. Additionally, sinkholes are collection areas for surface runoff which may carry other pollutants. The absence of an adequate soil cover at the bottom of the sinkhole means simply that water passing through the overlying rubble will not be filtered of harmful constituents before it enters solution channels beneath the depression. Once the pollutants have entered the groundwater regime, they may spread in unpredictable patterns to areas being tapped as water sources by unsuspecting well owners. Plate 12 pictures a typical sinkhole situation showing the high potential for contamination.

Exposures of carbonate bedrock on the land surface and areas in which only a very thin soil cover overlies carbonate bedrock afford excellent opportunities for groundwater contamination. As



Source: Virginia State Water Control Board — VRO

PLATE NO. 12

with sinkholes, the key factor is the lack of adequate soil cover to purge wastes from surface runoff.

Sources of Contamination. Though there have been no major areas of groundwater pollution identified in Shenandoah County, local contamination occurs occasionally. The most significant potential sources of groundwater contamination are septic tank drainfields; agricultural runoff from croplands, barnyards and feedlots; spills and leakage of petroleum and hazardous chemicals; and leakage from sanitary landfills and waste treatment facilities.

Septic tank systems are a common form of domestic sewage treatment in this County. If an inadequate soil cover houses the septic tank drainfield, pollutants will not be filtered out before they enter the groundwater. Nitrates and coliform bacteria are the most common contaminants from septic systems.

Agricultural runoff from croplands often causes nitrate contamination from fertilizers. In addition, pesticides and herbicides also may be negative factors. Barnyards and feedlots are also a common source of bacterial contamination.

Hydrocarbon contamination caused by spills and leakage of petroleum products has been reported in several areas of the County. Minute amounts of petroleum in groundwater may cause foul tastes and offensive odors. Occasionally the water returns to a normal state in a reasonable time if the source can be identified and eliminated. In many cases, however, it is impossible to determine the source of the contamination because petroleum products undergo drastic changes once they come in contact with rocks and soil.

Several incidents have occurred recently in Shenandoah County and are still under investigation. West of New Market, drainage pipes which apparently drain springs in the area have been found to be contaminated with some type of petroleum product, probably gasoline. The source is as yet unknown but is possibly one of several service stations in the immediate area. An incident in Edinburg involving a newly-drilled well at a local business establishment is possibly related to an old gasoline storage tank which has long since been removed from the ground. The tank at the time of removal was reported to be in a leaky state; gasoline which may have escaped from the tank likely has saturated the soil in the area and could be the source of the contamination.

Sanitary landfills and waste treatment facilities are potential sources of groundwater pollution. Industrial wastes often contain heavy metals which can be highly toxic in sufficient quantities. Landfills produce leachate, a "grossly polluted liquid characterized by high concentrations of dissolved chemicals, chemical and biological demand, and hardness" (Zaporozec, 1974). The key to pollution prevention is responsible management and operation of waste disposal facilities. Groundwater monitoring is an effective method of determining the presence and extent of contamination. Shenandoah County has exhibited no known groundwater pollution from any waste disposal sites, though most facilities have been in operation for many years.

## CHAPTER VI

## CONCLUSIONS AND RECOMMENDATIONS

## Conclusions

The groundwater resources of Shenandoah County are an important water supply source. Approximately half of the County's population is supplied by groundwater. Present groundwater development is confined mainly to the Central Valley area with the majority of the development being in the carbonate units. The Martinsburg Formation is a reliable water-bearing unit but has been developed to a lesser extent. Maximum potential is possible from the alluvial and terrace deposits overlying the carbonate rocks and the Martinsburg Formation. Present groundwater development can probably be tripled without adverse effects as long as responsible management practices are observed.

Groundwater quality is generally very good. High hardness is common from the carbonates and the Martinsburg Formation, and excessive iron concentrations are commonly found in the Silurian and Devonian shale and sandstone units in the east and west. The Martinsburg shale is unusual in that iron concentrations rarely exceed 0.3 mg/l.

No major groundwater contamination problems exist in Shenan-doah County. Isolated cases of local contamination are frequent and are usually the result of inadequate septic tank systems, agricultural runoff, or spills and leaks from petroleum facilities. Many potential pollution sources exist, and the areas underlain by

carbonate formations are the most susceptible to contamination due to the presence of solution channels.

## Recommendations

- (1) The alluvial and terrace deposits extending from New Market to Edinburg along the North Fork of the Shenandoah River and to the west of Edinburg offer the greatest groundwater potential and can likely be developed to yield several million gallons per day if responsible management practices are observed.
- (2) The Martinsburg Formation can be developed to a far greater extent and can be relied upon to produce good quality groundwater of moderate to good yields if well sites are selected to take maximum advantage of topography and geology.
- (3) The carbonate formations underlying the Central Valley offer fair to good groundwater potential. However, these formations are more susceptible to groundwater contamination due to the presence of solution channels.
- (4) Proper well development in the shale and sandstone formations along the West Virginia border, especially in the Basye area, will usually result in adequate supplies for domestic and small public and commercial uses.
- (5) The shale and sandstone formations of the Massanutten Range should be considered only for small domestic uses.
- (6) Hardness should be a consideration when developing supplies in the carbonate rocks and the Martinsburg Formation.
- (7) Excessive iron concentrations should be considered when developing the Silurian and Devonian shale and sandstone formations.

- (8) When the need to develop groundwater arises:
- (a) consulting hydrogeologists, well drillers and representatives of this Agency are available for information and advice;
- (b) the Virginia Department of Health must be contacted pursuant to developing a public supply well and should be contacted when developing a domestic drinking water supply;
- (c) reports and samples required by the Groundwater Act of 1973 must be submitted to the State Water Control Board.

## APPENDIX A

## KEY WATER WELLS IN SHENANDOAH COUNTY

The accompanying Shenandoah County map (Plate A-1) shows locations for approximately 150 of the more than 300 wells and springs indicated on the computer printout appearing in Appendix B. They are representative of the County as a whole as far as density is concerned. The numbers appearing next to each well/spring may be cross-referenced with the information contained in Appendices B and C.

## APPENDIX B

## SUMMARY OF WATER WELL DATA FOR SHENANDOAH COUNTY

The computer printout on the following pages lists basic data for wells and springs in Shenandoah County. This printout is updated frequently to include information from new Water Well Completion Reports which are constantly being submitted by water well drillers. The information under the heading "Aquifer" may be cross-referenced with Table 2, Chapter III. Locations for many of the wells may be found in Appendix A.

## VIRGINIA STATE WATER CONTROL BOARD BUREAU OF WATER CONTROL MANAGEMENT

SUMMARY OF WATER WELL DATA FOR SHENANDOAH COUNTY

THE FOLLOWING LIST OF WELL DATA SUMMARIZES BASIC DATA OBTAINED FROM WATER WELL COMPLETION REPORTS WHICH ARE ON PERMANENT FILE IN THE OFFICES OF THE VIRGINIA STATE WATER CONTROL BOARD. ADDITIONAL INFORMATION FOR MANY OF THE WELLS IS AVAILABLE AND CAN BE OBTAINED BY CONTACTING THE APPROPRIATE REGIONAL OFFICE OR THE BUREAU OF WATER CONTROL MANAGEMENT AT THE AGENCY HEADOUARTERS IN RICHMOND.

# \*\*\*\*\*\* EXPLANATION OF PARAMETERS \*\*\*\*\*\*\*

SWCB NO: STATE WATER CONTROL BOARD NUMBER - A SEQUENTIAL NUMBERING SYSTEM USED WITHIN A COUNTY; WHEN REFERRING TO A SPECIFIC WELL USE THIS NUMBER

OWNER AND/OR PLACE: IDENTIFIES ORIGINAL OR CURRENT WELL OWNER AND/OR LOCATION OF WELL

YEAR COMP: YEAR IN WHICH WELL CONSTRUCTION WAS COMPLETED

LOG: TYPE OF LOG ON FILE FOR WELL; U = DRILLERS, E = ELECTRIC, G = GEOLOGIC

ELEV: ELEVATION - MEASURED IN FEET ABOVE MEAN SEA LEVEL

TOTAL DEPTH: TOTAL DEPTH DRILLED, IN FEET, WITH RESPECT TO LAND SURFACE

BEDROCK: DEPTH TO BEDROCK, IN FEET, WITH RESPECT TO LAND SURFACE

ASING: MAXIMUM AND MINIMUM DIAMETER OF CASING, IN INCHES, USED IN WELL

DEVEL ZONE: DEVELOPED ZONE - INTERVALS, IN FEET, WHERE AQUIFERS TAPPED AND/OR SCREENED

AQUIFER: WATER-BEARING UNIT; ABBREVIATIONS USED INDICATE GEOLOGIC AGE OF UNIT AND ARE CONSISTENT WITH "GEOLOGIC MAP OF VIRGINIA" (DIVISION OF MINERAL RESOURCES - 1963)

STATIC LEVEL: DEPTH. IN FEET, TO WATER WITH RESPECT TO LAND SURFACE; MEASUREMENTS TAKEN WHEN WEN WELL IS NOT PUMPED AND ARE GENERALLY THOSE RECORDED ON COMPLETION DATE

YIELD: REPORTED OR MEASURED PRODUCTION. IN GALLONS PER MINUTE

DIFFERENCE, IN FEET, BETWEEN STATIC LEVEL AND PUMPING LEVEL: I.E., REPORTED MEASURED DROP. IN FEET, IN WATER LEVEL DUE TO PUMPING DRAWDOWN:

SPEC CAPAC: SPECIFIC CAPACITY - YIELD PER UNIT OF DRAWDOWN EXPRESSED AS GALLONS PER MINUTE PER FOOT OF DRAWDOWN

HOURS - DURATION OF PUMP TEST. IN HOURS, FROM WHICH THE PRECEDING THREE ITEMS WERE DERIVED HRS:

USE OF WATER OR WELL UNDER CONSIDERATION; DOM = DOMESTIC, PUB = PUBLIC, GOV = GOVERNMENT, IND = INDUSTRIAL, COM = COMMERCIAL, INS = INSTITUTIONAL, ABD = ARANDONED, DST = DESTROYED, IRR = IRRIGATION, RCH = ARTIFICIAL RECHARGE USE:

MANAGEMENT BOARD CONTROL CONTROL WATER STAT A U OF VIRGINIA ы ж ы

## WATER WELL DATA FOR SHENANDOAH COUNTY SUMMARY OF

USE	TO DO
HRS	40 22 32 43 43 53 53 53 53 54 54 55 56 57 57 57 58 58 58 58 58 58 58 58 58 58 58 58 58
SPEC	2.01 0.08 0.09 0.07 0.09 0.09 0.09 0.09 0.09
DRAW	50 1119 174 20 296 87 87 87 87 87 87 87 87 87 87 87 87 87
YIELD	450 2005 2005 2005 2005 2006 2006 2006 20
STATIC LEVEL	100
AQUIFER	000 000 000 000 000 000 000 000 000 00
ZONE TO	135 135 135 96 96 121 121 122 220 123 291 162 162 163 164 164 164 164 164 164 164 164 164 164
DEVEL FROM	203 126 95 126 120 120 120 120 161 161 161 162 163 164 165 165 165 165 165 165 165 165 165 165
CASING MAX MIN	0 6666 66 6668 1666 67 100 NO
BED- ROCK	2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
TOTAL DEPTH	1136 1136 1136 1136 1128 1128 1128 1128 1128 1128 1128 112
ELEV	810 810 810 945 1105 965 1115 980 940 940 940 940 940 940 940 940 940 94
P07	aaaa aaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaaa
YEAR	64 64 64 64 64 64 64 64 64 64 64 64 64 6
OWNER AND/OR PLACE	HOLLY FARNS #3 BURTON COMMAY #1 OAK LEAF PARK #1 TOWN OF EINBURG #3 VINGINIA I GRIM #2 JONES #1 SAMUEL M GARBER EVA SI GEST EMMETT KNOWLES #1 C W LONG #2 AL LACKAWS CALVIN WEATHERHOLTZ 2 FORT VALLEY ELEM #2 RAYMOND L END #1 FORT VALLEY ELEM #2 RAYMOND L SINE #1 ALLEARNES #1 COLOCAWS COLOCAWS COLOCAWS COLOCAWS FRENEST E HEFF HEARTY OF VA INC #1 EDGE HILL FAM INC #1 EDGE HILL FAM MS CONCORD MOBILE HOMES ROCCO FARMS #1 ROCCO FARMS #1 ROCCO FARMS #1 BOWMAN APPLE PROD #4 BOWMAN APPLE PROD #2 BOWMAN APPLE PROD #3 TOMS BRHAURERTOWN #2 TOMS BRHAURERTOWN #3 TOMS BRHAURERTOWN #3 TOWN OF NEW MARKET TOWN OF NEW MARKET TOWN OF NEW MARKET
SWCB NO	0.4844444444444444444444444444444444444

2 4

VIRGINIA STATE WATER CONTROL BOARD BUREAU OF WATER CONTROL MANAGEMENT

SWCB

0.000 0.000

	USE	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	2 2 2	
	SPEC	. 53 . 14 . 20 . 08 . 30 . 56
**************************************	DRAW	255 205 150 150 132 10
**************************************	YIELD	4 4 6 4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
	STATIC	175 175 180 995 112 30 30 55 56 56 56 56 56 56 56 56 57 58 58 58 58 58 58 58 58 58 58 58 58 58
R O L B O A P D A N A G E M E N T OAH COUNTY	AQUIFER	008 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
ν Σ Q *	ZONE TO	395 100 100 100 100 100 100 100 100 100 10
α q. \$	DEVEL FROM	390 400 400 400 400 1120 1120 1130 1130 1130 1130 1130 11
C 0 N T L DATA F:	CASING MAX MIN	αναροννοσο σοσοροσοσοσοσο σοσοσοσοσοσοσο
A T E & A T E & C C C C C C C C C C C C C C C C C C	BED- ROCK	18 10 10 10 10 10 10 10 10 10 10 10 10 10
S T A T W A T Y OF WAT	TOTAL DEPTH	1000 1000
1 A O F SUMMARY	ELEV	1090 1080 935 935 880 880 905 745 740 1000 1000 1000 1000 1000 1000 1000
Z D * *	907	
VIRGINIA ST BUREAU OF W SUMMARY OF	YEAR	88 8 8 7 7 1 1 2 8 4 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
***	OWNER AND/OR PLACE	MOUNTAIN WATER WORKS TOWN OF MT JACKSON #1 NEW MARKET BATTLEFLD BLUE RIDGE HOMES #2 BROYSELL MANTZ #1 EGORGE G RABBIT E M RITTENOUR M BRRDEN M BRRDEN M BRRDEN CARK LCARK LLOYD CLICK LESTER FOLTZ EM RITTENOUR M BRRDEN GRAY PHILLIPS MILLARD MINES RICHARD HOTTLE BONNALD JORDAN GARY HILLIPS MILLARD MINES MILLARD MINES MILLARD MINES BRYCE MOUNTAIN #8 BRYCE MOUNTAIN #8 BRYCE MOUNTAIN #8 BRYCE MOUNTAIN #7 HOWELL METAL CO #1 L M NEWLAND CO #1 BRH - ALONZAVILLE #2 WALTER CHRISMAN MALTER CHRISMAN MALTER CHRISMAN MALTER CHRISMAN ME MULLIKIN JERRY RYAN GEORGE SHIRKEY
	SWCB	998 998 998 998 998 998 998 998 998 998

## 2.00 DRAW 150 150 55 82 YIELD STATIC LEVEL 30 AGUIFER OF WATER WELL DATA FOR SHENANDOAH COUNTY CCO DR OMB OC OMB ZONE 113 77 156 76 141 522 321 441 621 71 71 71 71 71 71 73 115 140 300 DEVEL FROM 140 320 320 320 440 440 105 105 120 120 120 114 135 CASING MAX MIN BED-ROCK SUMMARY ELEV L06 CHARLES CUSTER WILLIAM C LAMBERT TOWN OF MT JACKSON WARREN L BARB FLOYD BAKER HARRY COOPER BARBARA CROWELL HENRY P HARRIS RICHARD HOTTLE WAYNE VIAR KEITH ZIRKLE BRH - EDINUUNG I #1 ALLEEN #1 (WOODSTOCK) IRAN LITTEN CONWAY WATERS CONWAY WATERS LARRY SHOWALTER ROBERT & LARRY SMITH C B SNYDER JR GEORGE GOOD OWNER AND/OR PLACE RONALD GISEWHITE LINDEN GOCHENOUR RAYMOND GOCHENOUR CHARLES GRIMM CHARLES ANDREWS DOUG BARRICK BARRICK BARRICK BARRICK BARNEY BUWRER DANIEL BURNER HOWAER CARDER J LEWIS CAMPBELL RALPH H COMBS WILMER DOVE J L FARREN GARL H FLEWING ALGER E GALLADAY DON GHEEN

USE

	USE	222222	E 8 E W E	W W W W W	W W W W	X X X X X X X X X X X X X X X X X X X	W W W W W W W W W W W W W W W W W W W	0000000	W W W W W O O O O O O O O O O
	T S S		<b>9</b> ,						12 3
	SPEC	• 01							
* * * * * *	DRAW	65						No.	
* * * * * * * * * * * * * * * * * * *	YIELO	8 50 6 1	0 0 0 0 ° 0	200 200 200 200 200 200 200 200 200 200	10 12 2	30 100 100	25 20 20 30 20 20 20 20 20 20 20 20 20 20 20 20 20	. w o o o o o	o ω 4 Ο ν
O L B O A R D N A G E M E N T COUNTY	STATIC LEVEL	10 30 30	40 20 150	8	30 10	20 80 30 15 15	30 30 75	50 90 20	22 102 73 70
0 L B N A G E COUNTY	AQUIFER	89 89 89 89 89 89 89 89 89 89 89 89 89 8	8 0 8 8 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0MB 0MB 0C0	90	CCO DR	8MO 000 000 000 000 000	8 00 0 0 00 0	000E 000E 040
CONTROOL MASHER	ZONE		96	95		221	201	135	191 326 155 430
*	DEVEL		95	. 4		220	200	120	190 325 150 429
A T E K C O N T R L DATA FOR	CASING MAX MIN	• • • • • • • •	o o o o	<b>ადად</b> ადად	)	· • • • • • • • • • • • • • • • • • • •	- - - -	σφοσφού	on a construction of
E E E E E E E E E E E E E E E E E E E	BED- ROCK	30	20 20 20 20 20 20 20 20 20 20 20 20 20 2	28.84.0 8.00.0 1.00.0	12,42	35 1 2 4 5	21 25 25 26 26 27 26 27 26 27 26 27 26 27 26 26 26 26 26 26 26 26 26 26 26 26 26	20 20 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	200000
S T A T W A T OF WAT	TOTAL DEPTH	75 90 248 503 165	96 124 117 220	218 128 165 165	228 228 97	265 248 248 232	157 165 73 720 97	96 218 218 78 157 100	328 328 155 430
N 1 A U O F SUMMARY	ELEV	1250	1065 865 950	1025			740 915 1310	1025	1245 900
E B B C C C C C C C C C C C C C C C C C	907	220 0	0220	20 000	2002	00000	000000	ع م م م م م	22020
2 2 ** 11 D ** 2 > 20 **	YEAR	72 72 75 75 75 75 75	12 2 2 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	72 42	73	42 42 43 43 43	4 5 5 5 5 5 7 5 7 5	112122	27 27 27 27 37
**************************************	OWNER AND/OR PLACE		LARRY LITTEN BRH-MASSNTN VIEW #1 WALTER H MEARS CLUNISE MCCLANAHAN	JAMES A MCDANIEL JAMES A MCDANIEL ROBERT L MORGAN ERWIN MORSETON ROHANNIRAY	L M NEWLAND L M NEWLAND CHARLES NICHOLSON ANDREW O'NEILL DONNIE ODER A LCH	REASON GEORGE DONALD NORMAN PATRICI			
	SECB NO	186 187 188 189 190	192 193 194 195	198 198 200 201	203 203 204 205	207 208 208 210 211	212 213 214 215 216 217	222 222 222 223 224	224 224 228 230 230

IRGINIA STATE WATER CONTROL BOARD BUREAU OF WATER CONTROL MANAGEMENT

USE

		γ ⊃ 20	F A	J OF SUMMARY	<b>3</b> L	A T E R WATER WEL	CUNT	<u>م</u> م	O L M A SHENANDOAH	N A G E	⊢ Z W ∑				
*******************	* * * *	* * * *	I	***	* * * *	****	*	*****	* * * * * * * * * * * * * * * * * * * *	***	***	***	*****		
OWNER AND/OR PLACE YEAR LOG EL	P07		W.	LE <	TOTAL DEPTH	BED- ROCK	CASING MAX MIN	DEVEL FROM	ZONE TO	AGUIFER	STATIC LEVEL	YIELD	DRAW	SPEC	H.S.
۵	۵		•	066	100	-	vo	06	91	DR DR	54	52			
1 0 27	00	-	96	080	225	15	<b>1</b> 0 <b>1</b> 0	194	195	98	65	15			
0 94		•	J	3	205	100	o vo	3	1	98		300			
76 0 1	0 0		10	010	40	9	<b>.</b>	82	83	0 M B	60 4	202			
U 52		۵ ۵			246	0.7	o •o	240	241	3 8	Ť	7 10			
0 92	0		~	160	471	20	m	390	391	OMB OMB		(M)			
		٥			463	2.0	vo v	463	464	90E	Ĺ	4 .			
0 1		<b>.</b>			201	2 5	D 4	* 6		2 5	90.	7 1			
00 75		۵۵			202	9 4	တ္	200	201	0.00 M. 0.00	·	7 4			
	c	_			501						9	~			
. 5 <i>T</i>	<b>)</b>				745	120	9			0M8	15	52			
89		06	90	S	49		9			000		ж С			
ETHEL HURLEY 66 670 FILVIN KIRLER 74 620		670	670		320		ď			0 11					
76 D	a		)		98	55	φ.			00E	21	12			
		٥			85	<b>-</b> - u	<b>9</b> 9	93%	61	DEV	ب 0 ر	m 4			
9.0	۵۵				145	20	<b>.</b>	140	141	00E	5	o o			
21 46	٥	_	1090	_	185	10	۰ ب	180	181	025		w,			
			138(	_	120	6 6	o •o	90	141	S E		12			
92	۰	•			452	9	9	350	351	0MB	110	œ .			
	0 0	163	1635		215	10	o •o	202	200	200	67	12			
3,4	٠,	;			307	30	<b>9</b> 0 v	300	301	080	110	φ.			
9.2	, 0	7	1631		185	25	, o vo	169	170	) e	06	* 0.			
R 76 D	۵				82	-	•	81	82	0M8	56	30			
76	۵ ۵		1045		256	10	<b>9</b> 0 4	250	251	90E	ū	200	4	S.00	
20 97	o C		711		2 -	2	· •	74	3 00	OMB OMB	100	Š			
92					132	35	) <b>v</b> o		125	00E	4.	S			
76		a			102	40	9	10	1010	OMB	S.	c			
92		٥۵			155	52	φ,	41.	5014	98	96	12			
I #2 76		<b>3</b> C			205	ر در ا	<b>o</b> 4	145	146	900	0	0 P			<b>†</b> †
9,4		ם נ			- 1 - 1 - 1 - 1 - 1	ر د بر	o «	140	141	e a	γ <b>τ</b>	2 O			
7.3	,	_	1025		375	<u>;</u>	<b>, 4</b> 0	) 	;	0 M B	) }	£			
JACK D COOPER 73 1010	_	1010	1010		126		ю 1			6 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		Č			
9		•			* 1		)					)			

## VIRGINIA STATE WATER CONTROL BOARD BUREAU OF WATER CONTROL MANAGEMENT

## SUMMARY OF WATER WELL DATA FOR SHENANDOAH COUNTY

S USE	11
SPEC HRS CAPAC	00*2
DRAW	4
YIELD	1100 1000 1000 1000 1000 1000 1000 100
STATIC LEVEL	2 2 2 2 3 3 3 3 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6
AGUIFER	### ### ##############################
ZONE TO	1001 1001 1001 1001 1001 1001 1001 100
DEVEL 7	165 165 165 165 165 165 165 165
CASING E	••••••••••••••••••••••••••••••••••••••
BED- C	110 110 110 110 110 110 110 110 110 110
TOTAL BI DEPTH RI	2000 2000 2000 2000 2000 2000 2000 200
ELEV	900 900 900 900 900 900 900 900
٦٥٥ ا	ع م م م م
YEAR	8 0 2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
OWNER AND/OR PLACE	RALPH HOSAFLOK BEVERLY POLK COOPER BROS TIRE CO SHENANDOAH TRACTOR SHEN CO LANDFILL SHEN-VALLEY HOMES BERLIN RYMAN JAMES V SORRELS WHOLESOME FOODS UNKNOWN TOM ESTEP JIMMY ROSEN TOM ENLINGER BRUCE M WILSON HELSLEY HOME JACK COOPER SUB #] JACK C
SWCB NO	22.2048474210088484846948469484444444444444444444444

USE

	ŦS.	4 M M M 4 M M M M M M M M M M M M M M M
	SPEC	41.
*	DRAW	S 0 2
*	YIELD	0 m m m m m m m m m m m m m m m m m m m
***	STATIC LEVEL	5 2 2 3 3 3 3 3 3 4 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6
SHENANDOAH COUNTY	AQUIFER	000 000 000 000 000 000 000 000 000 00
ANDOA+	ZONE TO	118
FOR SHEN	DEVEL	φ. 4 δ
DATA	CASING MAX MIN	
WATER WELL	BED- ROCK	145 10 20 20 10 20 20 20 20 20 20 20 20 20 20 20 20 20
7 OF WAT	TOTAL OEPTH	2005 2005 2005 2005 2005 2005 2005 2005
SUMMARY *****	ELEV	960 1080 1000 935 1000 760
*	907	
* * * * * * * * * * * * * * * * * * * *	YEAR	2 47474747474747474747474747474747474747
**************************************	OWNER AND/OR PLACE	HARRY E LONG CORP #2  RALPH REEDY JOHN DELLINGER PAUL NESSELRODT BETTY RUSH LEON F DELLINGER JOHNNY A RYMAN COOPER JOHNNY A RYMAN CECIL BORDER JOHNNY A RYMAN CELIFORD GEORGE JAKES B LAMBERT SR ZANE COFFELT JAKES B LAMBERT SR ZANE COFFELT JAKES B LAMBERT SR ZANE COFFELT JAKES B LAMBERT JOHN SMOOT JACK F DODSON SHAN FRAVEL COOPER BETTY MOOMAW TILLEN PHIPPS WAYNE MARKLEY GARFIELD PHIPPS WAYNE MARKLEY GARFIELD PHIPPS WAYNE MARKLEY GARFIELD PHIPPS WAYNE MARKLEY BETTY MOOMAW TILLINAN GEORGE BRILL BURGESS DELLINGER RICHARD DOSS HARRY COOPER W M SULLIVAN GEORGE BRILL DONNLD KEELER
	SWCB	$\begin{array}{llllllllllllllllllllllllllllllllllll$

VIRGINIA STATE WATER CONTROL BOARD BUREAU OF WATER CONTROL MANAGEMENT

## SUMMARY OF WATER WELL DATA FOR SHENANDOAH COUNTY

USE	
E S	44
SPEC	
DRAW	
YIELD	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
STATIC	2005 800 1000 1000 165 165 165 165 178 178 178
AQUIFER	00 00 00 00 00 00 00 00 00 00 00 00 00
ZONE TO	<b>601</b>
DEVEL	009
CASING MAX MIN	<b>0000000000000000000000000000000000000</b>
BED- ROCK	130 50 20 20 20 20 40 40 40 40 10
TOTAL DEPTH	250 1250 1777 1250 1250 1250 1250 1250 1250 1250 1250
ELEV	100
P00	
YEAR	211111111111111111111111111111111111111
OWNER AND/OR PLACE	EVERT MILLER  ALVIS SONNER  BETTY SHOWALTER  LAWRENCE BERRICK  RICHARD WETZEL  KENNETH JOHNSON  ELIZABETH FURN REC #2  FOREST HILLS SUB  RYMANS SUBDIVISION #1  RYMANS SUBDIVISION #2  BORDENS TRAILER PK #3  BORDENS TRAILER PK #3  BORDENS TRAILER PK #3  HEISHMANS TRAILER PK #3  HONDYTAIN VIEW #1  MOUNTAIN VIEW #1  ROUNDANCE HTN SUB #3  SUNDANCE HTN SUB #3  SUNDANCE HTN SUB #3  SUNDANCE HTN SUB #3  WESTBROOK SUBDIVISION  LAWRENCE V, HUFFMAN  BLUE RIDGE HOMES  HOWARD BROCK  H W DELLINGER & SONS  OTTO EVANS  FRED GEIGER  JAMES H KRANICH  WILLIAM H LOGAN  DONALD LYNCH  EDWARD L. MILLER  E W ROBERTS  FRED WHETZEL
SWCB	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0

## APPENDIX C

SUMMARY OF GROUNDWATER QUALITY ANALYSES FOR SHENANDOAH COUNTY

The computer printout on the following pages lists basic groundwater quality data available for certain of the wells and springs listed in the water well data summary (Appendix B).

Locations for many of the wells may be found in Appendix A.

## ٥ ⋖ 0 r Z 0 œ u S A I z .. 9 V 1 R

## w ۵ د S ٥ ш ۵ Z 4 SURVEILLANCE Ŀ 0 ⊃ **∢** ш œ $\supset$

**6**0

'n

SHENANDOAH COUNTY GROUNDWATER QUALITY ANALYSES FOR

SUMMARY OF

THE FOLLOWING LIST OF GROUNDWATER QUALITY DATA SUMMARIZES BASIC DATA OBTAINED FROM ANALYSES OF GROUNDWATER, COLLECTED FROM WELLS AND SPRINGS, WHICH ARE ON PERMANENT FILE IN THE OFFICES OF THE VIRGINIA STATE WATER CONTROL BOARD. ADDITIONAL GROUNDWATER QUALITY INFORMATION FOR MANY OF THESE WELLS AND SPRINGS IS AVAILABLE AND CAN BE OBTAINED BY CONTACTING THE APPROPRIATE REGIONAL OFFICE OR THE BUREAU OF SURVEILLANCE AND FIELD STUDIES AT THE AGENCY HEADQUARTERS IN RICHMOND.

# \*\*\*\*\*\*\*\* EXPLANATION OF PARAMETERS \*\*\*\*\*\*\*

STATE WATER CONTROL BOARD NUMBER - A SEQUENTIAL NUMBERING SYSTEM USED WITHIN A COUNTY; WHEN REFERRING TO A SPECIFIC WELL USE THIS NUMBER A COUNTY! WHEN REFERRING TO A SPECIFIC WELL USE SWCB NO:

WELL. P OWNER AND/OR PLACE: IDENTIFIES ORIGINAL OR CURRENT WELL OWNER AND/OR LOCATION

DATE SAMP: DATE SAMPLED - MONTH AND YEAR IN WHICH WATER SAMPLE WAS COLLECTED.

HYDROGEN ION CONCENTRATION - BASED ON A SCALE OF 1 THROUGH 14, WATER WITH A PH GREATER THAN 7.0 IS CONSIDERED TO BE BASIC OR ALKALINE; THE LARGER THE PH VALUE, THE MORE ALKALINE THE WATER. WATER WITH A PH LESS THAN 7.0 IS CONSIDERED TO BE ACIDIC; THE SMALLER THE PH VALUE, THE MORE ACIDIC THE WATER. SPECIFIC CONDUCTIVITY - AN INDICATOR OF THE RELATIVE AMOUNT OF DISSOLVED MINERALS IN WATER; HIGHER VALUES INDICATE GREATER AMOUNTS OF DISSOLVED MINERALS; UNIT OF MEASUREMENT IS MICROMHO COND SPEC

TOTAL DISSOLVED SOLIDS - INDICATES TOTAL AMOUNT OF DISSOLVED MINERALS IN WATER; UNIT OF MEASUREMENT IS MILLIGRAMS PER LITER T-DIS SOLID:

. AND OTHER TOTAL HARDNESS - CAUSED BY THE PRESENCE OF CALCIUM, MAGNESIUM, IRON, ZINC , ANT TRACE METALS, UNIT OF MEASURE IS MILLIGRAMS PER LITER. CALCIUM-MAGNESIUM HARDNESS - INDICATES THAT PORTION OF TOTAL HARDNESS CAUSED BY CALCIUM AND MAGNESIUM, WHICH ARE GENERALLY RESPONSIBLE FOR ALMOST ALL HARDNESS IN WATER, UNIT OF MEASURE IS MILLIGRAMS PER LITER. HARDNESS TOTAL: HARDNESS CA, MG:

THE AMOUNT OF HARDNESS IN WATER WILL AFFECT THE ABILITY OF SOAP TO LATHER OR CLEANSE BECAUSE OF THE TENDENCY OF THE IONS CAUSING HARDNESS OF WATER, THE MORE DIFFICULT IT IS FOR SOAP TO LATHER.

TOTAL HARDNESS IS GENERALLY DETERMINED BY CHEMICAL TITRATION WHEREAS CALCIUM-MAGNESIUM HARDNESS IS GENERALLY DETERMINED BY MATHEMATICAL CALCULATION FROM CHEMICALLY DETERMINED VALUES FOR CALCIUM AND MAGNESIUM. BECAUSE OF THIS DIFFERENCE IN DETERMINATION, THE CALCIUM-MAGNESIUM HARDNESS VALUES FOR SOME ANALYSES WILL BE LARGER THAN THE TOTAL HARDNESS VALUE. NOTE:

PARAMETERS LISTED BELOW ARE MEASURED IN MILLIGRAMS PER LITER \*\*\*\*\*\*

CHLORIDE CALCIUM Ç MANGANESE SODIUM 504: HCO3: BICARBONATE MAGNESION FE: IRON

NITRATE (AS NO3)

... NO3:

STUDIES BOARD VIRGINIA STATE WATER CONTROL

*****	**	***	MARY OF	GROUND#ATER	* * * *		ANAL YSES	ES FOR	SHEN	SHENANDOAH COUNTY	COUNTY	* * * * * *	* * * *			
SWCB OWNER AND/OH PLACE NO	DATE	Ţ	SPEC	1-01S SOLID	HARDNESS TOTAL CA:MG	M.G	ir A	ΣŽ	Š	S	A Z	*	нсо3	S04	ರ	N03
4 LEONARD E CAMPBELL #2	10 75	7.3	260	174	-	154 (	0.10	0.01	43.0	11.5	1.0	1.7			6.0	15.5
6 BURTON CONWAY #1	7 74	7.5	720	565	4	445 (	0.20		155.0	14.2	20.5	1.1			46.0	3.1
20 RAYMOND L SINE	7 74	7.5	650	397	,4	418 (	00.0		97.0	43.0	7.5	1.0			4.0	5.8
26 EDGE HILL FARM	11 75	7.3		539		131 (	00.0	00.0	0.64	2.3	1.0	1.6			7.0	25.2
27 CONCORD MOBILE HOMES	7 74	7.4	540	172	7	154 (	0.10		54.0	6.4	2.8	1.8			1.0	10.2
31 NORTHERN VA POULTRY	8 74	7.5	313	233	2	520 (	0.10		76.0	7.4	3.5	1.9			3.0	8.0
36 DAN COOKE #1	10 75	7.8	290	385	9	310 (	0.20	00.0	70.0	33.0	1.0	<b>7.</b> 0			7.0	
38 STONE SHOP REST #1	12 75	7.7	700	503	4	461 (	00.0	0.40	129.0	34.0	14.0	9.0			12.0	4.0
S7 VA DEPT OF HIGHWAY #1	9 J4	7.1	920	711	4	) 664	0.20		175.0	15.2	18.3	1.8			0.07	12.8
58 VA DEPT OF HIGHWAY #2	7 74	7.5	230	192	7	194 (	0.20		70.0	<b>4</b> .	3.5	8.0			1.0	7.1
59 VA DEPT OF HIGHWAY #3	9 74	7.4	350	257	8	205 (	0.10		63.0	11.7	4.8	2.0			18.0	16.8
60 AILEEN #1 (EDINBURG)	6 63	7.7			1	163	0.10	00.0	51.5	9.6	12.1		192	23.9	6.0	0.0
65 TOWN OF NEW MARKET #2		7.5			312 3	302	0.30	0.10	84.9	22.0	3.7	0.2		16.7	7.5	19.5
68 CHEMSTONE CORP	12 75	7.4	290	390	4	445	0.30	0.20	91.0	53.0	3.0	1:1			0.0	11.1
73 RICHARD MURRAY	8 74	7.4	251	177	-	163	0.10		5A.0	4.6	2+3	1.8			2.0	7.5
83 BRYCE MOUNTAIN #2	10 73	7.8	168	177	78	80	1.04	9.0	17.6	0.6	11.5	1.0		8.	2.0	0.0
84 BRYCE MOUNTAIN #1		7.9	218	168	104 1	103 (	09.0	00.0	26.3	9.3	14.0	1.0			3.0	0.0
91 ROBERT WEATHERHOLTZ	10 75	7.5	310	352	-	190	0.00	0.10	80.0	16.1	1.0	9.0			3.0	3.1
92 STONEWALL ELEM SCHOOL	2 76	7.1	240	185	7	141	0.10	00.0	31.0	15.5	3.0	9.0			12.0	17.7
93 MELVIN CLEM	6 75	7.2	650	416	un .	595	00.00	0.01	130.0	0.99	6.1	1.4			12.0	13.7
44 TOMMY JONES	10 75	0.2	700	557	4	924	00.0	00.0	110.0	37.0	1.0	1.2			20.0	50.9
95 EVERETTE LARKIN	10 75	7.4	630	461	4	400	0.00	0.01	88.0	0.44	1.0	5.0			11.0	35.4
96 MOUNTAIN WATER WORKS	5 72	e. a			154 1	153	1.24	0.15	47.2	R. 7	17.3	4.			0.3	0.0
NOTEALL ZEROS (00.00) - ANALY	ANALYSE	SED, NOT		DETECTED\$ ALL	NINES	(66*66)	1	COULD NOT	96	STORED, REFER TO	EFER TO	ANALYSIS	SIS	· a		

C - 4

VIRGINIA STATE WATER CONTROL BOARD BUREAU OF SURVEILLANCE AND FIELD STUDIES SUMMARY OF GROUNDWATER QUALITY ANALYSES FOR SHENANDOAH COUNTY

SWCB OWNER AND/OR PLACE	DATE	Ţ	SPEC	1-01S SOL 1D	HARDNESS TUTAL CA,MG	SS SA,MG	7. 1	Z	CA	MG.	A Z	¥	нс03	204	ರ	N03
98 NEW MARKET BATTLEFIELD 10 7	27 01 0	8.7			281	280	00.0	00.0	ec 80	65.9	1.1	1.1		15.0	5.6	2.2
102 HEARTY OF VA INC #2	10 75	7.4	320	222		198	00.0	00.0	64.0	<b>9.</b> 6	1.0	6.0			3.0	3.5
103 IRVIN INC	11 75	7.2		322		310	00.0	00.0	65.0	36.0	1.0	0.3			7.0	14.6
104 DUKE LUTZ	12 75	7.8	069	484		478	00.00	00.0	93.0	0.09	18.0	3.8			0.0	9.92
106 RUSSELL MANTZ #2	12 75	8.1	390	250		564	00.0	0.10	55.0	31.0	0.6	1.2			0.0	4.0
107 G G RABBIT	12 75	7.9	940	657	460	677	00.0	0.50	148.0	19.4	40.0	9.0			21.0	28.8
108 E M RITTENOUR	10 75	7.5		471		456	0.20	0.01	92.0	0.84	1.0	6.0			5.0	
109 M BORDEN	10 75	7.6	580	460		350	0.10	00.0	76.0	39.0	1.0	1.1			8.0	
110 HAROLD CLARK	10 75	7.4	640	531		338	0.40	62.0	107.0	17.5	3.0	2.0			1.0	
112 LESTER FOLTZ	10 75	6.3	82	61		32	00.0	77.0	0.6	2.4	1.0	0.3			5.0	1.3
116 DONALD JORDAN	6 75	7.4	420	283		692	00.0	00.0	65.0	26.0	2.8	1.0			.9	14.2
117 GARY PHILLIPS	11 75	7.8		152		122	00.0	00.0	29.0	12.2	10.0	0.0			3.0	0.0
120 LARRY RYMAN	92 9	7.2	320	198	172	203	00.0	00.0	72.0	5.9	5.0	1.3		4.1	0.4	7.1
121 GARY SHOWMAN	10 75	7.3	320	237		186	0.50	0.01	0.69	3.5	1.0	0.0			3.0	8.4
127 HOWELL METAL CO. #1	10 75	7.0	370	250		232	00.00	00.0	68.0	15.3	1.0	0.2			0.9	16.4
133 ELMER DELANDER	10 75	6.5	110	110		61	05*0	0.08	10.0	80 •	1.0	0.0			2.0	0.0
134 STEVE DELLINGER	12 75	7.5	170	148		11	6.20	1.25	12.0	10.2	12.0	6.0			0.9	0.0
136 DARYL FUNKHOUSER	10 75	7.7	240	433		344	0.30	0.04	112.0	15.8	1.0	3.6			8.0	
139 JERRY RYAN	10 75	7.4	470	347		295	0.10	00.0	0.46	14.9	1.0	2.7			10.0	56.6
140 GEORGE SHIRKEY	11 75	7.4		268		214	00.0	00.0	65.0	12.7	1.0	0.0			8.0	13,3
141 LLOYD SHIRKEY	11 75	7.2		183		149	0.30	0.01	50.0	0.9	1.0	0.0			4.0	5,3
142 LARRY SHOWALTER	10 75	7.3	310	440		191	3.70	0.20	56.0	12.7	1.0	1.1			2.0	0.0
143 ROBERT & LARRY SMITH	12 75	7.1	540	380		377	00.0	00.0	92.0	36.0	5.0	0.5			1.0	7.1

NOTE--ALL ZEROS (00.00) - ANALYSED. NOT DETECTED: ALL NINES (99.99) - COULD NOT BE STORED. REFER TO ANALYSIS

VIRGINIA STATE WATER CONTROL BOARD BUREAU OF SURVEILLANCE AND FIELD STUDIES SUMMARY OF GROUNDWATER QUALITY ANALYSES FOR SHENANDOAH COUNTY

	NO SAMP	Ŧ	SPEC	T-DIS SOLID	HARDNESS TOTAL CA.MG	11 12	Z Z	CA	¥	A A	¥	HC03	804	ე	NO3
ואו כים אוטבא טא	10 75	7.4	500	344	331	1 4.00	0.03	67.0	40.0	1.0	0.5			3.0	2.2
149 WARREN L BARB	10 75	6.9	10	223	121	1 5.00	2.00	37.0	7.1	1.0	0.0			1.0	0.0
151 HARRY COOPER	12 75	8.0	900	399	384	4 0.10	0.10	85.0	45.0	4.0	1.8			1.0	0.0
152 BARBARA CROMWELL	10 75	7.3	380	253	546	6 0.20	0.01	80.0	11.3	1.0	6.0			2.0	4.0
153 HENRY P HARRIS	12 75	7.9	310	210	190	0 0.10	0.10	6A.0	5.1	6.0	5.0			7.0	9,3
156 KEITH ZIRKLE	10 75	7.0	165	170	16	6 2.90	0.41	13.0	10.8	3.0	0.3			5.0	
167 BARNEY BURKE	10 76	6.5	280	169	112	2 0.20	0.51	24.0	12.9	13.0	4.0			3.0	0.0
185 CHARLES GRIMM	2 76	7.0	200	¥04	232	2 0.20	0.03	66.0	16.4	50.0	0.3			12.0	0.0
191 RAYMOND LINDAMOOD	12 75	7.7	640	465	411	1 0.10	0.10	86.0	48.0	11.0	1.4			14.0	23.0
192 LARRY LITTEN	1 76	7.2	630	389	327	7 1.80	0.07	114.0	10.4	6.0	0.5			13.0	1.3
194 WALTER MEARS	92 9	7.1	10	156	102 123	3 0.70	0.14	41.0	5.1	6.0	0.0	.•	21.7	. *	0.0
199 ROBERT L MORGAN	1 76	6.9	580	399	281	0.70	77.0	80.0	20.0	12.0	8.0			8.0	0.0
213 ROY SEAL	5 76	7.0	1150	983	950	0.30	0.13	196.0	15.0	47.0	5.0	4	400.5	39.0	0.0
216 GRANVILLE SIBERT	2 76	7.1	445	341	302	2 0.10	00.0	65.0	34.0	28.0	1.0			12.0	14.2
219 MELVIN STROOP	6 76	7.1	530	405	284 303	3 0.40	0.61	91.0	18.7	16.0	0.2	<b>=</b>	118.2	13.0	0.0
222 TREVA SAYLOR	1 76	7.3	540	354	257	7 0.20	0.19	73.0	18.3	12.0	8.0			13.0	0.9
230 OTTO L FULLER	5 76	7.0	680	463	417	7 0.10	0.01	103.0	39.0	12.0	1.7	4	497.8	18.0	7.5
235 GARY WAKEMAN	6 76	7.4	260	194	144 169	9 0.20	0.02	63.0	5.9	0.9	0.0		8.1	3.0	4.9
238 ROBERT TAYLOR	5 76	6.9	1300	1186	8448	3 0.20	0.12	150.0	18.0	48.0	7.1	3	481.4	10.0	0.0
245 G L FRAVEL	5 76	7.0	750	1070	775	3.20	0.19	250.0	37.0	41.0	8.0	7	482.4	6.0	0.0
247 ETHEL HURLEY	5 76	7.0	069	517	345	5 0.10	0.02	109.0	16.0	8.0	0.9	•	61.9	1.0	0.0
274 LINDA VARNEY	92 9	7.3	300	206	164 197	00.00	00.0	73.0	3.7	7.0	0.1		4.8	3.0	4.0
276 J SHERMAN	92 9	7.2	200	351	252 319	00.00	0.01	118.0	6.1	8.0	0.0		6.15	120.0	ກ

NUTE--ALL ZEROS (00.00) - ANALYSED, NOT DETECTED: MLL NINES (99.99) - COULD NOT BE STOKED, REFER TO ANALYSIS

VIRGINIA STATE WATER CONTROL BOARD BUREAU OF SURVEILLANCE AND FIELD STUDIE SUMMARY OF GROUNDWATER QUALITY ANALYSES FOR SHENANDOAH COUNTY

*********	李安帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝帝	*	* * * * *	***	***	*	* * * * *	****	****	***	***	* * * *	* * * *			
SWCB OWNER AND/OR PLACE	SAMP	Ţ	SPEC	T-DIS SOLID	T-DIS HARDNESS SOLID TOTAL CA•MG	.5.5 .4 • MG	iei iei	Z Ž	CA	<b>9</b> <b>Σ</b>	<b>4</b> 2	¥	нсо3	204	ე	N03
277 RALPH HOSAFLOK	6 76	7.0	76 7.0 330	526	210	221	221 0.00 0.00	00.0	86.0 1.8	1.8	5.0 0.0	0.0		5.9	2.0 3.1	3.1
278 BEVERLY POLK	92 9	7.3	310	212	76 7.3 310 212 178	195	00.0	00.0	195 0.00 0.00 72.0 3.8	3.8	0.0 0.6	0.0		3.9	5.0	5,3

NOTE--ALL ZEROS (00.00) - ANALYSED, NOT DETECTED; ALL NINES (99.99) - COULD NOT BE STORED, REFER TO ANALYSIS

## **GLOSSARY OF TERMS**

ALLUVIUM: A general term for sediments deposited during

recent geologic time by a stream or other body

of water.

ANTICLINE: An upward fold in rock strata.

AQUICLUDE: A geologic formation, group of formations or

part of a formation which is not permeable enough to furnish an appreciable supply for a

well or spring.

AQUIFER: A geologic formation, group of formations or

part of a formation capable of supplying water to wells and springs in usable quantities. An aquifer is unconfined (water table) or confined (artesian) depending on whether the groundwater level is at atmospheric pressure or greater than atmospheric pressure due to the presence of an

overlying, confining geologic formation (aquiclude).

BEDDING PLANE: The diversion plane in sedimentary or stratified

rocks which separates the individual layers, beds,

or strata.

BEDROCK: Any solid rock exposed at the surface or overlain

by unconsolidated materials.

CALCAREOUS: Containing calcium carbonate.

CARBONATE ROCK: A rock consisting chiefly of carbonate minerals

such as limestone and dolomite.

CATCHMENT: The area comprising the actual water intake area

for aquifer recharge and all areas that contribute

surface water to the intake area.

CLASTIC: Consisting of fragments of rocks or of organic

structures that have been transported mechanically to a place of deposition. Sandstone and shale are

the most common clastics.

COLLUVIUM:

Loose soil material or rock fragments deposited by the action of gravity, usually at the base of

a slope or cliff.

DIP:

The angle at which a rock bed is inclined from

the horizontal.

DRAWDOWN:

The measured difference between static level and pumping level in a well; the drop in the water

level due to pumping.

EVAPOTRANSPIRATION: A term embracing that portion of the precipitation returned to the air through direct evaporation or by transpiration of vegetation, no attempt being made

to distinguish the two.

FAULT:

A fracture or fracture zone along which there has been movement of two rock masses relative to one another parallel to the fracture. The movement may be a few inches or many miles, horizontal or

vertical.

FLOOD PLAIN:

The strip of relatively smooth land adjacent to a river channel and built of alluvium carried by the river during floods. The flood plain is covered by

water when the river is in flood.

FOLD:

A curve or bend in rock strata.

FORMATION:

A unit of geologic mapping consisting of a large

stratum of some one kind of rock.

FRACTURE:

Breaks in rocks due to intense folding or faulting.

GPD:

Gallons per day.

GROUNDWATER:

Water below the water table; water in the zone of

saturation.

HYDROLOGY:

The science that relates to the water of the earth.

IGNEOUS:

Rocks or minerals that solidified from molten rock

(magma).

IMPERMEABLE:

Having a texture which does not allow perceptible

movement of water through rock.

INTRUSIVE: Refers to igneous rocks which have penetrated into

or between older rocks while molten but have solidi-

fied before reaching the surface.

A fracture in rock along which no appreciable movement JOINT:

has occurred. Joints are generally perpendicular to

bedding planes.

KARST TOPOGRAPHY: Topography characterized by sinking streams, sinkholes,

caves and similar features indicative of underground

drainage developed through the solution of bedrock.

LITHOLOGY: The composition and structure of rock.

Refers to any rocks derived from pre-existing rocks **METAMORPHIC:** 

in response to pronounced changes of temperature.

pressure and chemical environment.

MGD: Million gallons per day.

Movement of water through the interstices of rocks PERCOLATION:

or soils except movement through large openings such

as solution channels.

The ability of a rock, sediment or soil to transmit PERMEABILITY:

water.

POROSITY: The property of a rock, soil, or other material of

containing spaces or voids.

PUBLIC SUPPLY: As defined by the Virginia Department of Health, a

water system serving more than 25 individuals or more

than 15 residential connections.

Depth to water in a well when the well is being pumped. PUMPING LEVEL:

The addition of water to an aquifer by natural infil-RECHARGE:

tration or artificial means.

That part of precipitation that appears in surface **RUNOFF:** 

streams. Groundwater recharge is that part of runoff

which has existed as groundwater since its last

precipitation.

SEDIMENT: Material borne and deposited by water.

SEDIMENTARY: Refers to rocks formed from the consolidation of

layered sediments that have accumulated in water.

SINKHOLE:

A funnel-shaped depression in the land surface, usually in limestone regions, developed by the dissolving action of water and connected with solution channels underlying the depression.

SOLUTION CHANNEL:

Joints or fractures in carbonate rocks which

have been enlarged by the dissolving action of water and which are capable of transmitting large quantities

of water.

STATIC LEVEL:

Depth to water in a well when the well is not being

pumped.

SYNCLINE:

A downward fold in rock strata.

TERRACE:

A level or gently inclined surface bordering a stream which represents a former level of the stream. Terraces are composed of alluvium produced by renewed downcutting

of the flood plain or valley floor by the stream.

UNCONSOLIDATED:

A sediment that is loosely arranged or unstratified, or

whose particles are not cemented together.

WATER TABLE:

The upper surface of the zone of rock or soil saturated

with groundwater.

## RIBLIOGRAPHY

The following list of references includes all those used in preparing this report in addition to several others which should provide educational reading on the subjects of groundwater resources and water well drilling.


- Aley, Thomas J., Williams, James H. and Massello, James W. <u>Groundwater</u>
  <u>Contamination and Sinkhole Collapse Induced By Leaky Impoundments in Soluble Rock Terrain</u>. Missouri Geological Survey and Water Resources, 1972.
- American Geological Institute. Dictionary of Geological Terms. 1957.
- American Geological Institute. Glossary of Geology. 1972.
- Army and Air Force, Departments of the. <u>Well Drilling Operations</u>. Technical Manual 5-297 and Air Force Manual 85-23, 1965.
- Ballentine, R. K., Reznek, S. R. and Hall, C. W. <u>Subsurface Pollution Problems in the United States</u>. U. S. Environmental Protection Agency, <u>Technical Studies Report TS-00-72-02</u>, 1972.
- Brent, William B. <u>Geology and Mineral Resources of Rockingham County</u>. Virginia Division of Mineral Resources, Bulletin 76, 1960.
- Butts, Charles. <u>Geology of the Appalachian Valley in Virginia</u>. Virginia Geological Survey, Bulletin 52, 1940.
- Cady, R. C. Ground-Water Resources of the Shenandoah Valley, Virginia. Virginia Geological Survey, Bulletin 45, 1936.
- Campbell, Michael D. and Lehr, Jay H. Water Well Technology. McGraw-Hill, 1973.
- Conservation and Economic Development, Department of. "Geologic Map of Virginia." Division of Mineral Resources, 1963.
- Conservation and Economic Development, Department of. <u>Ground Water in Virginia</u>. Division of Water Resources, Information Bulletin 502,1969.
- Conservation and Economic Development, Department of. <u>Potomac-Shenandoah</u> River Basin Hydrologic Analysis, Volume I. Division of Water Resources, Planning Bulletin 209, 1969.
- Conservation and Economic Development, Department of. <u>Potomac-Shenandoah</u> River Basin Hydrologic Analysis, Volume III. Division of Water Resources, Planning Bulletin 209, 1969.

Crockett, Curtis W. <u>Climatological Summaries for Selected Stations in</u> Virginia. Water Resources Research Center, 1972.

ì

- DeKay, Richard H. <u>Development of Ground-Water Supplies in Shenandoah</u>
  <u>National Park, Virginia</u>. <u>Virginia Division of Mineral Resources</u>,
  <u>Mineral Resources Report 10, 1972</u>.
- Douglas, Henry H. Caves of Virginia. Virginia Cave Survey, 1964.
- Flawn, Peter T. Environmental Geology. Harper and Row, 1970.
- Gibson, Ulrich P. and Singer, Rexford D. <u>Water Well Manual</u>. Premier Press, 1971.
- Halliday, William R. American Caves and Caving. Harper and Row, 1974.
- Hem, John D. <u>Study and Interpretation of the Chemical Characteristics of Natural Water</u>. United States Geological Survey, Water-Supply Paper 1473, 1970.
- Hinkle, Kenneth R. and Sterrett, R. McChesney. <u>Rockingham County Ground-</u> water. Virginia State Water Control Board, Planning Bulleting 300, 1976.
- Johnson, Edward E., Inc., <u>Ground Water and Wells</u>. Johnson Division, Universal Oil Products Company, 1966.
- Lohman, S. W. <u>Definitions of Selected Ground-Water Terms Revisions</u> and Conceptual Refinements. United States Geological Survey, Water-Supply Paper 1988, 1972.
- McKee, Jack E. and Wolf, Harold W. <u>Water Quality Criteria</u>. California State Water Resources Control Board, Publication 3-A, 1963.
- Meinzer, Oscar E. <u>Outline of Ground-Water Hydrology</u>. United States Geological Survey, Water-Supply Paper 494, 1923.
- National Water Well Association. "Water Well Driller's Beginning Training Manual." Published by the National Water Well Association, 1971.
- Newport, Thomas G. <u>Ground-Water Resources of Montgomery County, Pennsylvania</u>. Commonwealth of Pennsylvania, Department of Environmental Resources, 1971.
- Rader, Eugene K. and Biggs, Thomas H. <u>Geology of the Strasburg and Toms</u>
  <u>Brook Quadrangles, Virginia</u>. Virginia Division of Mineral Resources,
  Report of Investigations 45, 1976.
- Reeves, Frank. Thermal Springs of Virginia. Virginia Geological Survey, Bulletin 36, 1932.

- State Planning and Community Affairs, Division of. "Data Summary: Shenandoah County." Office of Research and Information, 1972.
- State Planning and Community Affairs, Division of. "Population Projections, Virginia Counties and Cities, 1980-2000." Economic Research Section, 1975.
- Thomas, H. E. The Conservation of Ground Water. McGraw-Hill, 1951.
- Todd, D. K. Groundwater Hydrology. John Wiley and Sons, 1959.
- Trainer, Frank and Watkins, Frank A., Jr. <u>Geohydrologic Reconnaissance</u> of the Upper Potomac River Basin. United States Geological Survey, Water-Supply Paper 2035, 1975.
- Virginia State Department of Health. "Waterworks Regulations, Public Drinking Water Supply." Bureau of Sanitary Engineering, 1974.
- Virginia State Water Control Board. "Guide for Water Well Contractors and Groundwater Users." Bureau of Water Control Management, Information Bulletin 508, 1974.
- Virginia State Water Control Board. "Ground Water in Virginia: Quality and Withdrawals." Bureau of Water Control Management, Basic Data Bulletin 38, 1973.
- Virginia State Water Control Board. "Rules of the Board and Standards for Water Wells." 1974.
- Virginia State Water Control Board. "State Water Control Law." Commonwealth of Virginia.
- Williams, James H. and Vineyard, Jerry D. "Geologic Indicators of Subsidence and Collapse in Karst Terrain in Missouri." Missouri Department of Natural Resources, 1976.
- Young, Robert S. and Rader, Eugene K. <u>Geology of the Woodstock, Wolf Gap, Conicville, and Edinburg Quadrangles, Virginia</u>. Division of Mineral Resources, Report of Investigations 35, 1974.
- Zaporozec, Alexander. <u>Hydrogeologic Evaluation of Solid Waste Disposal</u> in South Central Wisconsin. Wisconsin Department of Natural Resources, Technical Bulletin 78, 1974.



1;